

**2002 Cassini/INMS  
Ion and Neutral Mass Spectrometer**

**INMS STANDARD DATA PRODUCTS  
AND ARCHIVE VOLUME  
SOFTWARE INTERFACE SPECIFICATION  
(INMS Archive Volumes SIS)  
SIS ID: IO-AR-016**

David Gell and Greg Fletcher  
Space Physics Research Laboratory  
University of Michigan  
Ann Arbor, Mi 48109

and

S. Joy  
University of California, Los Angeles  
Los Angeles, CA 90095-1567

Version 1.1

September 16, 2005

**2002 Cassini/INMS  
Ion and Neutral Mass Spectrometer  
INMS STANDARD DATA PRODUCTS  
ARCHIVE VOLUMES  
SOFTWARE INTERFACE SPECIFICATION  
(INMS Archive Volumes SIS)  
Version 1.1  
September 16, 2005**

Approved:

---

J. H. Waite  
Team Leader

Date

---

Diane Conner  
Cassini Archive Data Engineer

Date

---

Ray Walker  
PDS Discipline Node Manager

Date

## Table of Contents

<b>1. PREFACE.....</b>	<b>1</b>	<b>APPENDIX A: DIRECTORY STRUCTURE FOR VOLUMES OF THE CO-S-INMS-3-L1A-U-V1.0 DATA SET ..</b>	<b>29</b>
1.1 DISTRIBUTION LIST	1	<b>APPENDIX B: DIRECTORY STRUCTURE FOR VOLUMES OF THE CO-S-INMS-2-PKT-U-V1.0 DATA SET..</b>	<b>31</b>
1.2 DOCUMENT CHANGE LOG	2	<b>APPENDIX C: CALIBRATION REPORT DIRECTORY STRUCTURE .....</b>	<b>32</b>
1.3 TBD ITEMS	3	<b>APPENDIX D: L1A STRUCTURE FILE CONTENTS .....</b>	<b>38</b>
1.4 ACRONYMS AND ABBREVIATIONS	3	<b>APPENDIX E: HKG STRUCTURE FILE CONTENTS .....</b>	<b>50</b>
1.5 GLOSSARY	4		
1.6 CONTENT OVERVIEW	4		
1.7 SCOPE	9		
1.8 APPLICABLE DOCUMENTS	9		
1.9 AUDIENCE	9		
<b>2. ARCHIVE VOLUME GENERATION .....</b>	<b>9</b>		
2.1 ARCHIVE STRUCTURE AND IDENTIFICATION	9		
2.2 DATA PRODUCTION AND TRANSFER METHODS	11		
2.3 ARCHIVE VOLUME CREATION	11		
2.4 VOLUME VALIDATION METHODS	12		
<b>3. ARCHIVE VOLUME CONTENTS .....</b>	<b>12</b>		
3.1 ROOT DIRECTORY CONTENTS	12		
3.2 INDEX DIRECTORY CONTENTS	13		
3.3 DOCUMENT DIRECTORY CONTENTS	13		
3.4 CATALOG DIRECTORY CONTENTS	14		
3.5 CALIB DIRECTORY CONTENTS AND NAMING CONVENTIONS	14		
3.5.1 <i>Required Files</i> .....	15		
3.5.2 <i>CALIB Directory Contents</i> .....	15		
3.6 DATA (STANDARD PRODUCTS) DIRECTORY CONTENTS AND NAMING CONVENTIONS	15		
3.6.1 <i>Required Files</i> .....	16		
3.6.2 <i>DATA Directory Contents</i> .....	16		
3.7 BROWSE DIRECTORY CONTENTS AND NAMING CONVENTIONS	16		
3.7.1 <i>Required Files</i> .....	17		
3.7.2 <i>BROWSE Directory Contents</i> .....	17		
3.8 EXTRAS DIRECTORY CONTENTS	17		
3.8.1 <i>SOFTWARE Directory Contents</i> .....	18		
3.8.2 <i>CALREPORT Directory Contents</i> ....	18		
<b>4. ARCHIVE VOLUME FORMAT.....</b>	<b>18</b>		
4.1 DISK FORMAT	18		
4.2 FILE FORMATS	18		
4.2.1 <i>Document File Formats</i> .....	18		
4.2.2 <i>Catalog File Formats</i> .....	18		
4.2.3 <i>PDS Label File Formats</i> .....	19		
4.2.4 <i>Data File Formats – Comma Separated Value Files</i> .....	19		
4.3 GENERAL DATA PRODUCT FORMAT	19		
4.3.1 <i>INMS SCI Data Product Formats</i> ....	19		
4.3.2 <i>INMS LIA Data Product Formats</i> ...	23		
4.3.3 <i>INMS HKG Data Product Formats</i> ..	23		
4.3.4 <i>INMS OTS Data Product Formats</i> ...	23		
4.3.5 <i>INMS HMD Data Product Formats</i> ..	26		

## 1. PREFACE

This document describes the contents and types of volumes belonging to all of the three INMS data sets.

### 1.1 Distribution List

<i>Table 1: Distribution List</i>	
<b>Name</b>	<b>Email</b>
Hunter Waite	hunterw@umich.edu
Greg Fletcher	gfletch@umich.edu
David Gell	david.a.gell@umich.edu
Ryan Miller	rpmiller@umich.edu
Rob Thorpe	rthorpe@swri.edu
Erin Walter	emwalter@umich.edu
Julia Xu	juliaxu@umich.edu
Vince Anicich	vincent.g.anicich@jpl.nasa.gov
Tom Cravens	cravens@kuphsx.phsx.ukans.edu
Wayne Kasprzak	wayne.kasprzak@gsfc.nasa.gov
Janet Luhman	jgluhman@sunspot.ssl.berkeley.edu
Ralph McNutt	ralph_mcnutt@jhuapl.edu
Wing Ip	wingip@jupiter.ss.ncu.edu.tw
Diane Conner	Diane.Conner@jpl.nasa.gov
Steve Joy	sjoy@igpp.ucla.edu
Robert Mitchell	Robert.Mitchell@jpl.nasa.gov
Dennis Matson	Dennis.L.Matson@jpl.nasa.gov
Linda Spilker	Linda.J.Spilker@jpl.nasa.gov

## 1.2 Document Change Log

<i>Table 2: Document Change History</i>		
<b>Change</b>	<b>Date</b>	<b>Affected Portions</b>
<ul style="list-style-type: none"> <li>Initial Draft</li> </ul>	01/20/2003	All
<ul style="list-style-type: none"> <li>updates based on review by J. Mafi</li> <li>Added L1A, and TTN data products</li> <li>Replaced target identifier E/J/S by S in data set names. No Earth or Jupiter Data</li> <li>Changed directory content tables to reflect the fact that all data is stored in a directories by day of year</li> </ul>	12/01/2004	
<ul style="list-style-type: none"> <li>Changed document number to reflect draft status, first approved version will be 1.0</li> <li>updates based on review by D. Conner</li> <li>omit event table product.</li> <li>detailed database schema deleted as unneeded</li> <li>Improve description of electronic data transfer</li> <li>Extensive changes based on discussions with discipline node,</li> <li>Deleted Geometry directory - unneeded</li> </ul>	02/15/05	
<ul style="list-style-type: none"> <li>Extensive changes based on discussions with discipline node,</li> <li>Update signature page, reflecting new PDS Project manager</li> <li>Update reference page to reflect current PDS documentation versions</li> <li>Expanded descriptions of volume structure</li> <li>Added map of PKT archive volume to appendices</li> <li>Simplification of production volume validation</li> </ul>	3/1/05	
<ul style="list-style-type: none"> <li>Add mission and instrument prefixes to CAT file names</li> <li>Correct typo's in Data Set Ids.</li> <li>Add instrument prefix to standard data product Ids</li> <li>Add PPI Spot check of production file structure</li> <li>Add EXTRA directory to L1A archive files</li> <li>Modify volume Ids to permit sequential runs of more than 1000 volumes</li> <li>Add calibration summary directory to reference volume</li> <li>Indicate that INMS_L1A volumes will contain calibration summaries valid at the time of volume creation.</li> </ul>	3/16/05	
<ul style="list-style-type: none"> <li>Move contents of reference volume to EXTRAS Directory on volume COINMS_3000</li> <li>Minor editorial changes</li> <li>Estimate of L1A data volume</li> <li>Added Appendix D, the L1A Structure</li> </ul>	3/31/2005	
<ul style="list-style-type: none"> <li>Reflects sample volume delivery</li> <li>changed speciality of outside peer reviewers</li> </ul>	4/15/2005	
<ul style="list-style-type: none"> <li>Peer review completed, changed target in data set names to S from SSA</li> </ul>	7/1/2005	
<ul style="list-style-type: none"> <li>Added Appendix E with housekeeping file format</li> </ul>	9/16/2005	Appendix E, section 4.3.3

### 1.3 TBD Items

Items that are currently TBD or not finalized, but will be defined in the next few months:

<i>Table 3: TBD Items</i>		
<b>Item</b>	<b>Section</b>	<b>Pages</b>
Monthly Data Volumes	1.6	9

### 1.4 Acronyms and Abbreviations

<i>Table 4: Acronyms and Abbreviations</i>	
<b>Acronym</b>	<b>Definition</b>
ASCII	American Standard Code for Information Interchange
CD-R	Compact Disc - Recordable Media
CD-ROM	Compact Disc - Read-Only Memory
CSN	INMS ion source, Closed Source Neutral
DVD	Digital Versatile Disc
GB	Gigabyte(s)
GSFC	Goddard Space Flight Center
INMS	Ion and Neutral Mass Spectrometer
ISO	International Standards Organization
JHU/APL	Johns Hopkins University / Applied Physics Laboratory
JPL	Jet Propulsion Laboratory
MB	Megabyte(s)
NSSDC	National Space Science Data Center
OSI	INMS ion source, Open Source Ion
OSNB	INMS ion source, Open Source Neutral Beam
OSNT	INMS ion source, Open Source Neutral Thermal
PDB	Project Database
PDS	Planetary Data System
PPI	Planetary Data System, Planetary Plasma Interactions Node
SDVT	Science Data Validation Team
SIS	Software Interface Specification
TBD	To Be Determined
UCLA	University of California, Los Angeles

## 1.5 Glossary

**Archive** – An archive consists of one or more Data Sets along with all the documentation and ancillary information needed to understand and use the data. An archive is a logical construct independent of the medium on which it is stored.

**Archive Volume** - An Archive Volume is a single physical media (CDROM, DVD, 9-track tape, etc.) used to permanently store files within the PDS archive. Archive Volumes may only be created on media approved by the PDS as meeting archive quality standards.

**Archive Volume Set** – A collection of one or more Archive Volumes used to store a single Data Set or collection of related Data Sets.

**Catalog Information** – High-level descriptive information about a Data Set (e.g., mission description, spacecraft description, instrument description), expressed in Object Description Language (ODL), which is suitable for loading into a PDS catalog.

**Data Product** – A labeled grouping of data resulting from a scientific observation, usually stored in one file. A product label identifies, describes, and defines the structure of the data. An example of a Data Product is a planetary image, a spectral table, or a time series table.

**Data Set** – A Data Set is a collection of Data Products from a single instrument that have a common data processing level, together with supporting documentation and ancillary files.

**Standard Data Product** – A Data Product generated in a predefined way using well-understood procedures, processed in "pipeline" fashion. Data Products that are generated in a non-standard way are sometimes called *special Data Products*.

## 1.6 Content Overview

The Ion and Neutral Mass Spectrometer (INMS) aboard the Cassini spacecraft consists of a closed ion source and an open ion source; various focusing lenses; an electrostatic quadrupole switching lens; a radio frequency quadrupole mass analyzer; two secondary electron multiplier detectors; and the associated supporting electronics and power supply systems. The INMS will be operated in three different modes: a closed source neutral mode (CSN), for the measurement of non-reactive neutrals such as  $N_2$  and  $CH_4$ ; an open source neutral (OSN) mode, for reactive neutrals such as atomic nitrogen; and an open source ion (OSI) mode, for positive ions with energies less than 100 eV. The primary focus of the INMS investigation is on the composition and structure of Titan's upper atmosphere and its interaction with Saturn's magnetospheric plasma. Note that the INMS 'Closed Source' mode only measures neutral particles so 'neutral' is redundant when referring to this mode. However CSN is used throughout this document so that file naming conventions are the same number of characters for all modes.

INMS is a complex instrument, and will be taking data continuously throughout the tour phase of the mission (the exception being the release of the Huygens Probe and the associated quiet period, during which most instruments on Cassini will be turned off). This complexity, coupled with tracking the minute changes in the characteristics of the instrument over time, mean calibration data and calibration techniques will be dynamic. For this reason it will be impractical to redeliver data volumes as calibration improves. The solution is to deliver a data set that has scaling factors applied (i.e. converted to engineering units), and provide the calibration data as a separate ancillary volume. Thus, as calibrations improve, only the reference volume will need to be redistributed.

Each of the three modes of the INMS will produce packets containing total counts per sample. The number of integration periods that are co-added to form a packet depends on the rate at which the instrument is taking data.

INMS data will be divided into three data sets, one containing telemetry packet contents converted from data numbers to engineering units, one containing detector data annotated with instrument state and geometric data, and a third containing higher level data produced from the lower level data. The data sets may contain one or more product types, which correspond to collections of related data in files of specific organization. The two high level data sets contain one product type apiece, whilst the low level data set contains one product type for each telemetry packet. The data set identification, CODMAC levels, and product types are enumerated in Table 5.

<i>Table 5: Relationship Between Data Sets and Standard Data Products</i>			
<b>Data Set ID</b>	<b>CODMAC Level</b>	<b>Standard Data Product ID</b>	<b>Description</b>
CO-S-INMS-5-TTN-C-V1.0	5	INMS_TTN	Profiles of species densities
CO-S-INMS-3-L1A-U-V1.0	3	INMS_L1A	Annotated instrument output
CO-S-INMS-2-PKT-U-V1.0	2	INMS_PKT_SCI	Telemetry Packets with contents converted from data numbers to dimensional quantities
		INMS_PKT_HKG	
		INMS_PKT_HMD	
		INMS_PKT_SMD	
		INMS_PKT_OTS	Operational table description

The data set CO-S-INMS-2-PKT-U-V1.0 contains the contents of the INMS telemetry packets, with each variety of packet forming a product type. INMS produces 4 packet types, Science (SCI), Housekeeping (HKG), Science Memory Dumps (SMD), and Housekeeping memory Dumps (HMD). An additional data type, OTS, is included in this data set which contains information describing the operational table set controlling the data collection.

The data set CO-S-INMS-3-L1A-U-V1.0 contains annotated detector signals as a single data type. The data is aggregated from the science and housekeeping telemetry, spacecraft ephemeris and attitude data, Saturnian system ephemeris, and operations table contents. This data is provided as the fundamental data from which to produce higher level products. Besides the data files, this data set includes graphical browse products and a calibration summary valid at the time of volume creation.

It is anticipated that the data set CO-S-INMS-5-TTN-C-V1.0 containing altitude profiles of atmospheric species abundances, will be produced from data analysis performed by the INMS science team and archived on a best-effort basis. The contents of this data set is related to Titan's atmosphere and will contain profiles of both neutral and ion species, included in Table 6 and Table 7, along with derived temperature profiles. Additional data product types may be added to this data set as the analysis results merit. Possibilities include magnetospheric ion and neutral flux as a function of look direction, space, and energy for each species. Magnetospheric constituents which INMS is capable of detecting, consist largely of water products: For the inner



magnetosphere, ions such as  $\text{H}_3\text{O}^+$ ,  $\text{H}_2\text{O}^+$ ,  $\text{O}^+$ ,  $\text{H}^+$ ,  $\text{OH}^+$ , and neutrals such as  $\text{H}_2\text{O}$ ,  $\text{H}$ ,  $\text{OH}$ ,  $\text{O}$  (though  $\text{OH}$  and  $\text{O}$  are both highly reactive neutrals, and thus may not be present at detectable levels). For the outer magnetosphere, ions such as  $\text{H}^+$ ,  $\text{N}^+$ ,  $\text{N}_2^+$ ,  $\text{H}_2\text{CN}^+$  and/or  $\text{C}_2\text{H}_5^+$ , and neutrals such as  $\text{N}$ , and  $\text{N}_2$ . At the icy satellites, INMS expects to detect species similar to those in the inner magnetosphere, along with additional trace species.

**Table 6: Most Abundant Ion Species in Titan's Ionosphere**

Mass Group	Mass Number	Species
Light	1	H <sup>+</sup>
	2	H <sub>2</sub> <sup>+</sup>
	3	H <sub>3</sub> <sup>+</sup>
Medium	14	N <sup>+</sup> , CH <sub>2</sub> <sup>+</sup>
	15	CH <sub>3</sub> <sup>+</sup> , NH <sup>+</sup>
	16	CH <sub>4</sub> <sup>+</sup>
	17	CH <sub>5</sub> <sup>+</sup>
Heavy	27	C <sub>2</sub> H <sub>3</sub> <sup>+</sup>
	28	N <sub>2</sub> <sup>+</sup> , C <sub>2</sub> H <sub>4</sub> <sup>+</sup> , HCNH <sup>+</sup>
	29	N <sub>2</sub> H <sup>+</sup> , C <sub>2</sub> H <sub>5</sub> <sup>+</sup>
Very Heavy	39	C <sub>3</sub> H <sub>3</sub> <sup>+</sup>
	41	C <sub>3</sub> H <sub>5</sub> <sup>+</sup> , H <sub>5</sub> <sup>+</sup>
	51	C <sub>4</sub> H <sub>4</sub> <sup>+</sup>
	52	C <sub>3</sub> H <sub>2</sub> N <sup>+</sup>
	53	C <sub>4</sub> H <sub>5</sub> <sup>+</sup> , C <sub>5</sub> H <sub>5</sub> <sup>+</sup> , C <sub>5</sub> H <sub>5</sub> <sup>+</sup>
	65	C <sub>5</sub> H <sub>5</sub> <sup>+</sup>
	67	C <sub>5</sub> H <sub>7</sub> <sup>+</sup>
	69	C <sub>5</sub> H <sub>9</sub> <sup>+</sup>
77	C <sub>6</sub> H <sub>5</sub> <sup>+</sup>	
79	C <sub>6</sub> H <sub>7</sub> <sup>+</sup> , C <sub>5</sub> H <sub>5</sub> N <sup>+</sup>	
91	C <sub>7</sub> H <sub>7</sub> <sup>+</sup>	

**Table 7: Expected Neutral Species in Titan's Upper Atmosphere**

Mass Number	Closed Source	Open Source Neutral
2	H <sub>2</sub>	
3	HD	
4	He	
14		N
15		NH
16	CH <sub>4</sub>	CH <sub>4</sub> , O
17	<sup>13</sup> CH <sub>4</sub>	OH
18	H <sub>2</sub> O	H <sub>2</sub> O
26	C <sub>2</sub> H <sub>2</sub>	
27	HCN	HCN
28	N <sub>2</sub> , C <sub>2</sub> H <sub>4</sub> , CO	N <sub>2</sub> , C <sub>2</sub> H <sub>4</sub> , CO
29	<sup>15</sup> N <sup>14</sup> N, <sup>13</sup> C <sub>2</sub> H <sub>4</sub>	
30	C <sub>2</sub> H <sub>6</sub>	
36	( <sup>36</sup> Ar)	
39		CHCN
44	CO <sub>2</sub> , C <sub>3</sub> H <sub>8</sub>	
50		C <sub>3</sub> N
51	CH <sub>3</sub> CN, HC <sub>3</sub> N	
52	C <sub>2</sub> N <sub>2</sub>	
74		C <sub>6</sub> H <sub>2</sub>
76	C <sub>4</sub> N <sub>2</sub>	
78	C <sub>6</sub> H <sub>6</sub>	

Table 8 contains a list of targeted flybys for which INMS is currently prime. When INMS is the prime instrument, the spacecraft pointing design was specified by the INMS team to support INMS data collection goals. The inner magnetosphere passes are still being determined in the science planning process, thus this list stops at Rev 46 (where the planning process is at the time this document was written). However, since these types of encounters are typically on the order of 90 minutes to two hours, this will be a relatively small subset of the INMS data.

**Table 8: INMS Targeted Flybys**

Target	FLYBY	REV	Alt (Km)
Titan	A	A	1200
Titan	T5	6	951
Titan	T17	28	950
Titan	T18	29	950
Titan	T21	35	950
Titan	T26		
Titan	T27	41	952
Titan	T32	46	950
Titan	T36	50	950
Titan	T37	52	950
Titan	T39	54	952
Titan	T40	55	950
Enceladus	E61	61	TBD
Inner Mag		25	
Inner Mag		26	
Inner Mag		29	
Inner Mag		31	
Inner Mag		34	
Inner Mag		43	
Inner Mag		46	

In addition to the data sets outlined above, INMS will be producing and archiving a reference volume. This volume will contain the documentation that describes the INMS instrument and investigation. It will also contain the detailed calibration report. This report, contained in the CALIBRATION directory is the structured collection of document files, data files, command sequences and programs used to perform the characterizations of the flight and engineering model. Additional engineering model characterization activities are possible. In that event, the calibration report will be extended and the reference volume re-issued.

Table 9 contains estimates of the INMS monthly deliverable data volume, as well as a maximum possible. The L1A volume is computed based on INMS operating at full telemetry rate approximately 3 days per month and at reduced rate for the remainder of the period. Browse product files are negligible in volume compared with the data files.

<i>Table 9: Deliverable Products and Their Approximate Size</i>			
<b>Data Set Identifier / Volume</b>	<b>Standard Data Product Type</b>	<b>Delivery Frequency</b>	<b>Estimated Size</b>
CO-S-INMS-2-PKT-U-V1.0	INMS_PKT_SCI	monthly	tbd
	INMS_PKT_HKG		tbd
	INMS_PKT_HMD		tbd
	INMS_PKT_SMD		tbd
	INMS_PKT_OTS		tbd
CO-S-INMS-3-L1A-U-V1.0	INMS_L1A	monthly	3.2GB

## 1.7 Scope

This specification applies to all archive volumes containing INMS data products for the duration of its mission.

## 1.8 Applicable Documents

*Planetary Science Data Dictionary Document*, August 28,2002, Planetary Data System, JPL D-7116, Rev. E.

*Planetary Data System Archive Preparation Guide*, January 20, 2005, JPL D-31224, Version 0.050120.

*Planetary Data System Standards Reference*, August 1, 2003, Version 3.6. JPL D-7669, Part 2.

*The Cassini Ion and Neutral Mass Spectrometer*, To appear in Space Science Review 2003, J. H. Waite et al.

*Cassini/Huygens Program Archive Plan for Science Data*, PD 699-068, JPL D-15976

## 1.9 Audience

This specification is useful to those who wish to understand the format and content of the INMS PDS data product archive collection. Typically, these individuals would be software engineers, data analysts, or planetary scientists.

## 2. ARCHIVE VOLUME GENERATION

### 2.1 Archive Structure and Identification

PDS data set names shall conform to the following format: CASSINI <target> INMS <data type> <calibration state> DATA V<major version>.<minor version>. For example, version one of the L1A science data set will be named CASSINI S INMS L1A UNCALIBRATED DATA V1.0.

PDS data set identifiers (dsid) will be abbreviated versions of the data set names formed according to the PDS formation rule for the DATA\_SET\_ID keyword. For example, the dsid for the data set above would be CO-S-INMS-3-L1A-U-V1.0.

Each data set making up the INMS archive is contained in a distinct set of physical volumes. At the PPI node, each data set is maintained on-line. The off-line archive for each data set consists

of a series of volumes, each bearing a unique volume identifier. The volume identifiers consist of the mission and instrument prefix and a volume identification number as follows:

COINMS\_Dnnn

where COINMS is the instrument prefix, D indicates the data set to which the volume belongs and nnn is a sequential number assigned to each volume. The values for the data set indicator are specified in the Table 10.

<b>Table 10: Volume Identifiers</b>		
<b>Data Set ID</b>	<b>Data Set Indicator <i>D</i></b>	<b>Example</b>
CO-S-INMS-2-PKT-U-V1.0	0	COINMS_0001
CO-S-INMS-3-L1A-U-V1.0	3	COINMS_3001
CO-S-INMS-5-TTN-C-V1.0	6	COINMS_6001

Data file names are formed from the date and type of the data according to the convention in Table 11. The names of INMS\_SCI, INMS\_L1A, and INMS\_TTN type files, which contain one hour of data contain the hour in the file names. The names of the remaining data types, produced once per day, have “00” in the hour field of the name. All file names include a version number, which is a sequentially assigned number, beginning at 01. The version number is incremented when the contents or format of the file is changed. The relationship between the various identifiers is illustrated in Table 12.

<b>Table 11: Data File Naming Convention</b> <i>Filename format: yyyydddhh_ttt_vv.CSV</i>		
<b>Identifier</b>	<b>Description</b>	<b>Options</b>
yyyydddhh	Start time of data file	yyy - Year ddd - Day of Year hh - Hour
ttt	Data type	L1A - Science data annotated with ancillary data TTN - Titan atmosphere profiles SCI - Science Data Packet contents, scaled HKG - Housekeeping Data Packet contents, scaled HMD - Housekeeping Memory Dump Packet Contents, scaled SMD - Science Memory Dump Packet Contents, scaled OTS - Operational Table Descriptions
vv	Version number of data	01, 02, ..., etc.

Each archive volume has the same general structure, consisting of a set of fixed top level directories, INDEX, DOCUMENT, CATALOG, CALIB, DATA, BROWSE and optionally EXTRAS, the contents of which will be described in detail below. The BROWSE directory is only part of the CO-S-INMS-3-L1A-U-V1.0 data set. The EXTRAS directory contains files that

are helpful but not required for interpretation of the archived data. Only the INDEX, DOCUMENT, CATALOG, EXTRAS and CALIB directories will exist only on the first physical volume of a data set to avoid the requirement to redistribute all physical volumes if the contents of either the EXTRA or CALIB directories change.

The relationship between the data set, standard data product identifiers and file names are illustrated in Table 12. The data structures for the archive volumes for data set are shown in the Appendixes.

<i>Table 12: Relationship Between Data Sets, Standard Data Product Types, and File Names</i>			
<b>Data Set ID</b>	<b>CODMAC Level</b>	<b>Standard Data Product ID</b>	<b>Example File Name</b>
CO-S-INMS-5-TTN-C-V1.0	5	INMS_TTN	200430015_TTN_01.CSV
CO-S-INMS-3-L1A-U-V1.0	3	INMS_L1A	200430015_L1A_01.CSV
CO-S-INMS-2-PKT-U-V1.0	2	INMS_PKT_SCI	200430000_SCI_01.CSV
		INMS_PKT_HKG	200430000_HKG_01.CSV
		INMS_PKT_OTS	200430000_OTS_01.CSV
		INMS_PKT_SMD	200430000_SMD_01.CSV
		INMS_PKT_HMD	200430000_HMD_01.CSV

## 2.2 Data Production and Transfer Methods

The INMS standard product archive collection is produced by the INMS instrument team in cooperation with the PDS Planetary Plasma Interactions (PPI) Node at the University of California, Los Angeles (UCLA). The INMS team is funded by NASA through the Cassini Project office and the PPI activities are funded by the NASA Planetary Data System.

The INMS team produces the individual data files and the associated PDS labels for each of the standard data products defined in section 1.6 above. Data files will all be comma-separated value, ASCII files containing all data of the appropriate type for the time interval contained in the data product. Data products will be compressed (Gzipped) and transferred via secure FTP to the PPI node. Each data transfer is logged in the Cassini Archive Tracking System, CATS. Upon notification of the data transfer provided by the CATS, the PPI node decompresses the transfer and compares its contents against the CATS transfer information. Each data file is validated against the MD5 checksum contained the corresponding detached label. The PPI node will post a positive or negative acknowledgement of the data receipt on CATS. If the acknowledgement is positive, no further action is required on the part of INMS. If the acknowledgement is negative, the transfer is repeated.

## 2.3 Archive Volume Creation

PPI collects the data files and labels provided by the INMS team onto archive volumes. Each archive volume contains all INMS data available for the time interval covered by the archive volume. Once all of the data files, labels, and ancillary data files are organized onto an archive volume, PPI adds all of the PDS required files (AAREADME, INDEX, ERRATA, etc.) and produces the physical media.

## 2.4 Volume Validation Methods

Validation of the INMS data archive is completed in two phases. The first phase is performed by the PPI node and consists of reviewing a sample data set for compliance with the PDS standards. The INMS team will submit a set of data files following the procedure of section 2.2 above. Upon receipt, the PPI node will confirm the structure of the files and labels. Once the sample data is validated, PPI will develop software to generate subsequent data volumes in an automated fashion.

The second phase of the validation consists of a peer review to ensure usability and completeness. The peer review panel will consist of members of the instrument team, the PPI and Central Nodes of the PDS, and at least two outside scientists actively working in the field of mass spectrometry or planetary atmospheres. The PDS personnel will be responsible for validating that the archive volume(s) are fully compliant with PDS standards. The instrument team and outside science reviewers will be responsible for verifying the content of the data set, the completeness of the documentation, and the usability of the data in its archive format. Any deficiencies in the archive volume will be recorded as liens against the product by the review panel. After all liens placed against the product or the product generation software are resolved, automated production and validation can begin.

Once automated production begins, the data file content will be spot checked by members of the INMS team. Browse products corresponding to the L1A product will be produced routinely and examined by members of the INMS team. In addition, the data will be actively used by team members to perform their analysis. Any discrepancies in the data noted during these activities will be investigated. If the discrepancy is a data error, the response will depend on the source of the error. If the error is in the software producing the data product, the error will be corrected and the data products affected will be reproduced. If there is a correctable error in a data file, the file will be replaced. If an error in a data file is uncorrectable, the error will be described in the cumulative errata file included on each volume in the volume set. The structure of data files and labels will be spot checked by the PPI node for compliance with PDS standards and this SIS.

## 3. ARCHIVE VOLUME CONTENTS

This section describes the contents of the INMS standard product archive collection volumes, including the file names, file contents, file types, and organizations responsible for providing the files. The complete directory structures are shown in Appendix A, B, and C. All directories and ancillary files described herein appear on each INMS archive volume, except where noted.

### 3.1 Root Directory Contents

The following files are contained in the root directory, and are produced by the PPI Node at UCLA. With the exception of the hypertext file and its label, all of these files are required by the PDS Archive Volume organization standards.

<i>Table 13: Root Directory Contents</i>		
File Name	File Contents	Provided By
AAREADME.TXT	This file completely describes the Volume organization and contents (PDS label attached).	PPI

<i>Table 13: Root Directory Contents</i>		
<b>File Name</b>	<b>File Contents</b>	<b>Provided By</b>
AAREADME.HTM	Hypertext version of AAREADME.TXT (top level of HTML interface to the Archive Volume).	PPI
AAREADME.LBL	A PDS detached label that describes AAREADME.HTM.	PPI
ERRATA.TXT	A cumulative listing of comments and updates concerning all INMS Standard Data Products on all INMS Volumes in the Volume set published to date.	PPI
VOLDESC.CAT	A description of the contents of this Volume in a PDS format readable by both humans and computers.	PPI

### 3.2 INDEX Directory Contents

The following files are contained in the index directory and are produced by the PDS PPI Node. The INDEX.TAB file contains a listing of all data products on the archive volume. In addition, there is a cumulative index file (CUMINDEX.TAB) that lists all data products in the INMS archive volume set to date. The index and index information (INDXINFO.TXT) files are required by the PDS volume standards. The index tables include both required and optional columns. The cumulative index file is also a PDS requirement; however, this file is not reproduced on each data volume. An online and web accessible cumulative index file is maintained at the PPI Node while archive volumes are being produced. Only the last archive volume in the volume series will contain a cumulative index file.

<i>Table 14: Index Directory Contents</i>		
<b>File Name</b>	<b>File Contents</b>	<b>Provided By</b>
INDXINFO.TXT	A description of the contents of this directory	PPI
INDEX.TAB	A table listing all INMS Data Products on this Volume	PPI
INDEX.LBL	A PDS detached label that describes INDEX.TAB	PPI

### 3.3 DOCUMENT Directory Contents

The document directory contains documentation that is considered to be either necessary or simply useful for users to understand the archive data set. These documents are not necessarily appropriate for inclusion in the PDS catalog. Documents may be included in multiple forms (ASCII, PDF, MS Word, HTML with image file pointers, etc.). PDS standards require that any documentation deemed required for use of the data be available in some ASCII format. Clean HTML is acceptable as ASCII formats in addition to plain text. The following files are contained in the DOCUMENT directory and are produced or collected by the PPI Node.



<i>Table 15: Document Directory Contents</i>		
<b>File Name</b>	<b>File Contents</b>	<b>Provided By</b>
DOCINFO.TXT	A description of the contents of this directory	PPI
VOLSIS.DOC	The Archive Volume SIS (this document) in Microsoft Word format	INMS, PPI
VOLSIS.ASC	The Archive Volume SIS (this document) in ASCII format	INMS, PPI
VOLSIS.LBL	A PDS detached label that describes VOLSIS.ASC, VOLSIS.HTM and VOLSIS.DOC.	PPI
Other Documents	Additional documents describing data processing, calibration etc.	INMS
Other Document labels	Detached PDS labels for any additional documents	PPI

### 3.4 CATALOG Directory Contents

The completed PDS catalog files in the catalog directory provide a top-level understanding of the Cassini/INMS mission and its data products. The data set catalog files (e.g. CO\_INMS\_PKT\_DS.CAT) will be provided by the INMS team, and the CATINFO.TXT by the PPI Node.

<i>Table 16: Catalog Directory Contents</i>		
<b>File Name</b>	<b>File Contents</b>	<b>Provided By</b>
CATINFO.TXT	A description of the contents of this directory	PPI
CO_INMS_PKT_DS.CAT or CO_INMS_L1A_DS.CAT or CO_INMS_TTN_DS.CAT	PDS Data Set catalog description of appropriate to the data set	INMS
CO_INSTHOST.CAT	PDS instrument host (spacecraft) catalog description of the Cassini spacecraft	Cassini Project
CO_INMS_INST.CAT	PDS instrument catalog description of the INMS instrument	INMS
CASSINI_MISSION.CAT	PDS mission catalog description of the Cassini mission	Cassini Project
CO_INMS_PERSON.CAT	PDS personnel catalog description of INMS Team members and other persons involved with generation of INMS Data Products	INMS
CO_INMS_REF.CAT	INMS-related references mentioned in other *.CAT files Additional bibliographic references, as appropriated	INMS
PRJREF.CAT	Cassini-relative references mentioned in other *.CAT files.	Cassini Project

### 3.5 CALIB Directory Contents and Naming Conventions

The calibration directory, included in the CO-S-INMS-3-L1A-U-V1.0 data set only, contains one or more spreadsheets of instrument calibration data. An additional file will be added when the instrument characteristics have either changed or been more precisely determined. The files

will be named according to their time range of applicability. For example, if it is determined that the calibration after 2007-030 is sufficiently changed, a file incorporating that date in its name will be added. The naming convention is defined in Table 17, below. To avoid the requirement of redistributing all physical media data volumes in the event of a calibration update, the CALIB directory will be present on only the first physical volume COINMS\_3000, and a note to that effect will be placed in the AAREADME file on all physical volumes.

Detailed documentation of the preflight characterization is contained in the EXTRAS directory.

<b>Table 17: Calibration Summary File Naming Convention</b> <i>Filename format: yyyyddd_CAL_vv.CSV</i>		
<b>Identifier</b>	<b>Description</b>	<b>Options</b>
yyyyddd	Date of validity	yyy - Year ddd - Day of Year
vv	Version number of data	01, 02, ..., etc.

### 3.5.1 Required Files

The calibration directory contains a file named INFO.TXT that is an ASCII text description of the CALIB directory contents. The calibration summary files will be described by detached PDS labels. The label files will have the same root name as the calibration file that they describe with the suffix “.LBL” replacing the “.CSV” suffix.

### 3.5.2 CALIB Directory Contents

The calibration data is organized in a flat directory structure, with the CALIB directory containing all of the calibration summary files and their labels.

<b>Table 18: Calibration Summary Directory Contents</b>		
<b>File Name</b>	<b>File Contents</b>	<b>Provided By</b>
INFO.TXT	Brief description of directory contents and naming conventions.	PPI
*CAL*.CSV	Calibration summary file.	INMS
*CAL*.LBL	PDS label for CAL file of same base name.	INMS

## 3.6 DATA (Standard Products) Directory Contents and Naming Conventions

The data directory contains the actual data products produced by the INMS team. The CO-S-INMS-2-PKT-U-V1.0 archive volumes will have SCI, HKG, OTS, EVT, SMD, and HMD files in daily subdirectories. The CO-S-INMS-3-L1A-U-V1.0 archive volumes will have L1A files in daily subdirectories. (see 3.6.2. for details description of this directory structure).

### 3.6.1 Required Files

Every subdirectory beneath the data directory contains a file named INFO.TXT that is an ASCII text description of the directory contents. Every file in the Data path of an Archive Volume must be described by a PDS label. All labels will be detached, having the same root name as the file they describe with the suffix “.LBL”. In directories where there are multiple data files with the same internal table structure, the table column description is included in a single format file (.FMT) that is referenced by a pointer within each PDS label file. This prevents the needless repetition of information that is not changing within the PDS label files.

### 3.6.2 DATA Directory Contents

The data directory contains a separate subdirectory for each day. The daily subdirectories are grouped by year into yearly directories. The structure may be seen in Appendix A. The yearly directories will be named for the year, 2004, 2005, and so forth. The daily subdirectories will be named with the ordinal day-of-year, 001, 002,...366. There may be more than one SCI, or L1A data file in each subdirectory, depending on what events take place on a given day. For HKG, OTS, SMD and HMD only one file will be produced per day. In addition to the data files there will be a brief text file (INFO.TXT) that describes the directory contents.

**Table 19: Daily Data Directory Contents**

File Name	File Contents	Provided By
INFO.TXT	Brief description of directory contents and naming conventions.	PPI
yyyydddhh_ttt_vv.CSV	Data file.	INMS
yyyydddhh_ttt_vv.LBL	PDS label for data files of same base name.	INMS
ttt_STRUCT_VV.FMT	PDS format file containing the data file structure portion of the PDS label for all of the INMS_L1A and INMS_SCI data files.	INMS
<i>ttt is replaced with L1A on the CO-S-INMS-3-L1A-U-V1.0 data set volumes  SCI,HKG, OTS, SMD, and HMD on the CO-S-INMS-2-PKT-U-V1.0 data set volumes  There are no structure files for standard data products INMS_HKG, INMS_OTS, INMS_SMD, or INMS_HMD</i>		

### 3.7 BROWSE Directory Contents and Naming Conventions

The browse directory contains images of INMS summary data and is included only on CO-S-INMS-3-L1A-U-V1.0 data set volumes. Two type of images are included, mass-time spectra and time series data. Each image spans six hours beginning at 0h, 6h, 12h, and 18h. (examples to be added). The image files are all portable network graphics files. The files are named in accordance with the convention in Table 20.

<b>Table 20: Browse Product File Naming Convention</b> <i>Filename format: yyyydddhh_ttt_vv.PNG</i>		
<b>Identifier</b>	<b>Description</b>	<b>Options</b>
yyyydddhh	Start date file	yyy - Year ddd - Day of Year hh - Hour of Day
ttt	Plot type	SPECTRA - mass-time spectra LINE - mass time series
vv	Version number of data	01, 02, ..., etc.

### 3.7.1 Required Files

Every subdirectory beneath the browse directory contains a file named INFO.TXT which contains a description of the directory contents in ASCII text. Every file in the browse path is described by a PDS label. All labels will be detached, having the same root name as the file they describe with the suffix '.LBL' replacing the suffix of the file name.

### 3.7.2 BROWSE Directory Contents

The browse directory contains a separated subdirectory for each day. The daily subdirectories are grouped by year into yearly directories. The structure may be seen in Appendix A. The yearly directories will be named for the year, 2004, 2005, and so forth. The daily subdirectories will be named with the ordinal day-of-year, 001, 002,...366. Each daily directory contains eight files, four mass-time spectra and four mass time series. In addition there will be a brief text file (INFO.TXT) that describes the directory contents.

<b>Table 21: Daily Browse Product Directory Contents</b>		
<b>File Name</b>	<b>File Contents</b>	<b>Provided By</b>
INFO.TXT	Brief description of directory contents and naming conventions.	PPI
yyyydddhh_SPECTRA_vv.PNG	Mass-time spectra browse plots	INMS
yyyydddhh_SPECTRA_vv*.LBL	PDS label for SPECTRA plot file of same base name.	PPI
yyyydddhh_LINE_vv.PNG	Time series browse plots	INMS
yyyydddhh_LINE_vv.LBL	PDS label for LINE plot file of same base name	PPI

## 3.8 EXTRAS Directory Contents

The EXTRAS directory contains files that are helpful, but are not required to interpret the INMS data. Files in the EXTRAS directory are exempt from labeling requirements. An EXTRAS directory is included in the CO-S-INMS-3-L1A-U-V1.0 archive. Subdirectories are used to organize the items into groups of related files. The EXTRAS directory will contain two subdirectories, SOFTWARE and CALREPORT. To avoid the requirement of redistributing all

physical media data volumes in the event that the EXTRAS contents changes, this directory will be present on only the first physical volume COINMS\_3000, and a note to that effect will be placed in the AAREADME file on all physical volumes.

### 3.8.1 SOFTWARE Directory Contents

The SOFTWARE directory contains a library of IDL routines that may be used to read, manipulate and display the contents of the L1A data files. In addition to the IDL source code files, the directory will contain a user's guide and an HTML help file.

### 3.8.2 CALREPORT Directory Contents

The calibration report directory in the EXTRAS directory contains the complete report of the pre-launch instrument characterization. The report is in the form of a structured series of files containing data from one characterization test. These files are the source for the initial calibration summary file included in the archive volume. The organization of this directory is shown in Appendix C.

## 4. ARCHIVE VOLUME FORMAT

This section describes the format of the INMS standard product archive volumes. Data that comprise the INMS standard product archives will be formatted in accordance with Planetary Data System specifications.

### 4.1 Disk Format

Disk formats for the archive volumes will conform to the PDS standard for the applicable media. At present, the plan is to archive INMS data on DVD-R media.

### 4.2 File Formats

The following section describes file formats for the kinds of files contained on Archive Volumes. For more information, see the PDS Archive Preparation Guide.

#### 4.2.1 Document File Formats

Document files with the .TXT suffix exist in all directories. They are ASCII files with attached PDS labels. All document files contain variable-length, 80-byte maximum records, with a carriage return character (ASCII 13) in the 79th byte and a line feed character (ASCII 10) in the 80th byte. This allows the files to be read by the MacOS, DOS, Windows, UNIX, OS2, and VMS operating systems.

However, some of the documents in the reference volume contain formatting and figures that cannot be rendered as pure ASCII text. These documents will be provided in formats that support graphics, such as HTML, MS Word, PDF, etc. The PDS requirement that all documentation critical to the understanding of the data set be provided in ASCII text form will be met by the inclusion of CLEAN HTML formatted documents.

#### 4.2.2 Catalog File Formats

Catalog files (suffix .CAT) exist in the Root and Catalog directories. They are formatted in an object-oriented structure consisting of sets of 'keyword = value' declarations. All files are

ASCII and conform to the same structure standards (line length, line terminator) as the PDS labels described in the next section.

#### 4.2.3 PDS Label File Formats

All data files in the INMS Standard Product Archive Collection have PDS labels. INMS is producing ASCII comma separated value files for all products. Each file will have an detached label, whose name is identical to the data file name with the .CSV suffix replaced by .LBL.

A PDS label, whether attached or detached from its associated file, provides descriptive information about the associated file. The PDS label is an object-oriented structure consisting of sets of 'keyword = value' declarations.

All detached labels contain 80-byte fixed-length records, with a carriage return character (ASCII 13) in the 79th byte and a line feed character (ASCII 10) in the 80th byte. This allows the files to be read by the MacOS, DOS, Windows, UNIX, OS2, and VMS operating systems.

#### 4.2.4 Data File Formats – Comma Separated Value Files

Delimited field, ASCII data files (.CSV suffix) exist in the DATA directories. These files are formatted for direct reading into many database management systems on various computers. In the INMS application of the delimited field format, fields are separated by commas. Records vary in length in bytes but will have a fixed number of fields. Missing data are represented by empty fields. All fields are described by detached PDS labels.

### 4.3 General Data Product Format

All INMS data products are CSV files that contain a series of homogenous records. Records are delimited by the end-of-line characters, the carriage return character (ASCII 13) followed by the line feed character (ASCII 10). Each file contains one or more lines of column headers. The starting location of the data is indicated in the label by the spreadsheet pointer. The column headers are the same as the field name in the tables below, additional header rows contain the units and strings to use as axis labels in plots. Blank fields indicate that the field is not applicable in the context of the record, the data is not available, is out of nominal range, or is otherwise not suitable for archiving. The following sections describe the content and structure of each of the standard data products within the INMS data sets, as described in Table 12 in Section 2.1.

#### 4.3.1 INMS SCI Data Product Formats

Table 22, below, describes the contents and ranges of the SCI data files. These files contain the contents of the science data packets, converted to dimensional quantities. Each record consists of 9 header items followed by the contents of the telemetry packet.

<i>Table 22: SCI Data File Contents and Structure</i>			
<b>Field Name</b>	<b>Type</b>	<b>Units</b>	<b>Range</b>
OriginalPacketID	integer		
EventID	integer		
PacketID	integer		
AssocSciPacketID	integer		

<i>Table 22: SCI Data File Contents and Structure</i>			
Field Name	Type	Units	Range
SCLKTime	string		
SCLKRaw	real		
ERTTime	string		
Processedtime	string		
Mode	string		
Valid	integer		$0 \leq x \leq 1$
MiniPktID	integer		$0 \leq x \leq 65535$
ElapsedSeqTime	integer		$0 \leq x \leq 65535$
ScanIndex	integer		$0 \leq x \leq 31$
SeqTable	integer		$0 \leq x \leq 31$
CycleNum	integer		$0 \leq x \leq 63$
IL1DAC	integer		$0 \leq x \leq 255$
C6DAC	integer		$0 \leq x \leq 15$
ThPresDAC	integer		$0 \leq x \leq 15$
CF1DAC	integer		$0 \leq x \leq 15$
BADAC	integer		$0 \leq x \leq 15$
DT1DAC	integer		$0 \leq x \leq 15$
DT2DAC	integer		$0 \leq x \leq 15$
EM1DAC	integer		$0 \leq x \leq 255$
EM2DAC	integer		$0 \leq x \leq 255$
TmModelIndex	integer		$0 \leq x \leq 31$
MassTable	integer		$0 \leq x \leq 2047$
IP1C1	real		$0 \leq x \leq 33711902.01$
IP1C2	real		$0 \leq x \leq 33711902.01$
IP2C1	real		$0 \leq x \leq 33711902.01$
IP2C2	real		$0 \leq x \leq 33711902.01$
•   •   •	• • •	• • •	$0 \leq x \leq 33711902.01$
IP67C1	real		$0 \leq x \leq 33711902.01$
IP67C2	real		$0 \leq x \leq 33711902.01$
IP68C1	real		$0 \leq x \leq 33711902.01$
IP68C2	real		$0 \leq x \leq 33711902.01$
Spare	integer		$0 \leq x \leq 65536$
Loop	integer		0, 1
Sthi	integer		0, 1

<i>Table 22: SCI Data File Contents and Structure</i>			
<b>Field Name</b>	<b>Type</b>	<b>Units</b>	<b>Range</b>
DCONState	integer		$0 \leq x \leq 63$
CycleIndex	integer		$0 \leq x \leq 255$
SequenceRecord	string		
CycleRecord	string		
FilCmd4On	integer		0, 1
FilCmd3On	integer		0, 1
FilCmd2On	integer		0, 1
Fil4Cmd1On	integer		0, 1
Fil6On	integer		0, 1
Fil4On	integer		0, 1
Fil3On	integer		0, 1
Fil2On	integer		0, 1
Fil1On	integer		0, 1
FilCollision	integer		0, 1
FilEmissAdjust	integer		0, 1
USeqFilError	integer		0, 1
Spare	integer		$0 \leq x \leq 511$
SciRTICounter	integer		$0 \leq x \leq 65535$
SciDTCCounter	integer		$0 \leq x \leq 65535$
SciSTMCounter	integer		$0 \leq x \leq 65535$
CPUIdleCounter	integer		$0 \leq x \leq 15$
Disc0Reset	integer		0, 1
AllSysGo	integer		0, 1
AllSysGoLatched	integer		0, 1
ExcNoHandler	integer		0, 1
SafeMode	integer		0, 1
ForcedSleep	integer		0, 1
BIU_Auto_Init	integer		$0 \leq x \leq 7$
GSETest	integer		0, 1
SystemInitialized	integer		0, 1
SystemConfigured	integer		0, 1
INMSBitFail	integer		0, 1
TMBuffOverflow	integer		0, 1
AlfBoot	integer		0, 1
AlfError	integer		0, 1
BIUMemError	integer		0, 1



<i>Table 22: SCI Data File Contents and Structure</i>			
<b>Field Name</b>	<b>Type</b>	<b>Units</b>	<b>Range</b>
ODBfrOverflow	integer		0, 1
USeqoOffline	integer		0, 1
USeqiOffline	integer		0, 1
USeqError	integer		0, 1
1750ME	integer		0, 1
AmuxError	integer		0, 1
CDSoOffline	integer		0, 1
CDSiOnline	integer		0, 1
CDSError	integer		0, 1
RTEError	integer		0, 1
bSpare	integer		0, 1
Imon1	real	A	$0.087772 \leq x \leq 1.646842$
BACollector	real	V	$-0.04 \leq x \leq 5.06$
Imon2	real	A	$0.087772 \leq x \leq 1.646842$
BACurrent	real	A RMS	$-0.010828 \leq x \leq 1.369742$
BAEmission	real	$\mu$ A	$103.302002 \leq x \leq 193.595596$
RFAGC	real	V	$-0.04 \leq x \leq 5.06$
MultAna1	real	$\mu$ A	$-0.08 \leq x \leq 10.12$
MultAna2	real	$\mu$ A	$0.258 \leq x \leq 1.518$
Imon3	real	A	$0.087772 \leq x \leq 1.646842$
ThermPressInt	real	V	$-0.04 \leq x \leq 5.06$
1Emission	real	$\mu$ A	$5.8812 \leq x \leq 25.6542$
3Emission	real	$\mu$ A	$-0.2022 \leq x \leq 25.5783$
EM1Current	real	$\mu$ A	$-0.30072 \leq x \leq 38.04108$
EM2Current	real	$\mu$ A	$7.518 \leq x \leq 38.04108$
CmdsRec	integer		$0 \leq x \leq 65535$
CmdsRej	integer		$0 \leq x \leq 65535$
AlfsRec	integer		$0 \leq x \leq 65535$
AlfsRej	integer		$0 \leq x \leq 65535$
CmdSerNo1	integer		$0 \leq x \leq 255$
Time1	integer		$0 \leq x \leq 16777215$
CmdSerNo2	integer		$0 \leq x \leq 255$
Time2	integer		$0 \leq x \leq 16777215$
CmdSerNo2	integer		$0 \leq x \leq 255$
Time3	integer		$0 \leq x \leq 16777215$

<i>Table 22: SCI Data File Contents and Structure</i>			
Field Name	Type	Units	Range
CRC	integer		n/a

#### 4.3.2 INMS L1A Data Product Formats

The L1A files contain the annotated science data. These files contain data abstracted from the science and housekeeping packets along with derived ancillary quantities. The data contained in these files is the basic data from which higher order products are derived. The structure file, included as Appendix D, further describes these records.

#### 4.3.3 INMS HKG Data Product Formats

The HKG files contain the complete contents of the housekeeping telemetry packets, converted to dimensional quantities. Each record consists of 9 header items followed by the contents of the telemetry packet. The structure file, included as Appendix E, further describes these records.

#### 4.3.4 INMS OTS Data Product Formats

The OTS is the Operations Table Set that was in instrument memory when the data was taken. Table 23 below describes the contents of the OTS data files. Each row in the file contains the description of a table set and its period of use. If more than one table set was in use during a day, this file will have multiple records.

<i>Table 23: OTS Data File Contents and Structure</i>	
Field Name	Type
TABLESETID	Integer
OPSTABLESTYPEID	Integer
CREATEID	Integer
CREATEDATE	Date/Time
UPDATEID	Integer
UPDATEDATE	Date/Time
INSTRUMENT	String
ACTIVE	Integer
ACTIVEDATE	Date/Time
INACTIVEDATE	Date/Time
LOCKED	Integer
TITLE	String
DESCRIPTION	String

#### 5.3.5 INMS SMD Data Product Formats

The SMD files contain the complete contents of the science memory dump telemetry packets. The INMS team uses this file to verify the state of the instrument. Table 24 below describes the contents and ranges of the SMD data files. These files contain the contents of the memory dump telemetry packets, converted to dimensional quantities, where appropriate. Each record consists of 9 header items followed by the contents of the telemetry packet.

<i>Table 24: SMD Data File Contents and Structure</i>			
Field Name	Type	Units	Range
OriginalPacketID	integer		
EventID	integer		
PacketID	integer		
SCLKTime	string		
SCLKRaw	real		
ERTTime	string		
Processedtime	string		
Mode	string		
Valid	integer		0, 1
MiniPacketID	integer		$0 \leq x \leq 65535$
DumpSource	integer		$0 \leq x \leq 7$
NumberOfWords	integer		$0 \leq x \leq 255$
DumpAddress	string		$0 \leq x \leq 65535$
IL1DAC	integer		$0 \leq x \leq 255$
C6DAC	integer		$0 \leq x \leq 15$
ThPressDAC	integer		$0 \leq x \leq 15$
CF1DAC	integer		$0 \leq x \leq 15$
BADAC	integer		$0 \leq x \leq 15$
DT1DAC	integer		$0 \leq x \leq 15$
DT2DAC	integer		$0 \leq x \leq 15$
EM1DAC	integer		$0 \leq x \leq 255$
EM2DAC	integer		$0 \leq x \leq 255$
TMMModelIndex	integer		$0 \leq x \leq 31$
MassTable	integer		$0 \leq x \leq 2047$
Word0	integer		$0 \leq x \leq 0xFFFF$
•   •   -	• • -		$0 \leq x \leq 0xFFFF$
Word170	integer		$0 \leq x \leq 0xFFFF$
WordSpare	string		
CPUIdleCounter	integer		$0 \leq x \leq 15$
Disc0Reset	integer		0, 1

<i>Table 24: SMD Data File Contents and Structure</i>			
Field Name	Type	Units	Range
AllSysGo	integer		0, 1
AllSysGoLatched	integer		0, 1
ExcNoHandler	integer		0, 1
Safemode	integer		0, 1
ForcedSleep	integer		0, 1
BIU_Auto_Init	integer		0, 1
GSETest	integer		0, 1
SystemInitialized	integer		0, 1
SystemConfigured	integer		0, 1
INMSBitFail	integer		0, 1
TMBuffOverflow	integer		0, 1
AlfBoot	integer		0, 1
AlfError	integer		0, 1
BIUMemError	integer		0, 1
ODBfrOverflow	integer		0, 1
USeqoOffline	integer		0, 1
USeqiOffline	integer		0, 1
USeqError	integer		0, 1
1750ME	integer		0, 1
AmuxError	integer		0, 1
CDSoOffline	integer		0, 1
CDSiOnline	integer		0, 1
CDSError	integer		0, 1
RTEError	integer		0, 1
Spare	integer		0, 1
Imon1	real	A	$0.087772 \leq x \leq 1.646842$
BaCollector	real	V	$-0.04 \leq x \leq 5.06$
Imon2	real	A	$0.087772 \leq x \leq 1.646842$
BaCurrent	real	A RMS	$-0.010828 \leq x \leq 1.369742$
BaErrission	real	$\mu$ A	$103.302002 \leq x \leq 193.595596$
RFAGC	real	V	$-0.04 \leq x \leq 5.06$
MultAna1	real	$\mu$ A	$-0.08 \leq x \leq 10.12$
MultAna2	real	$\mu$ A	$0.258 \leq x \leq 1.518$
Imon3	real	A	$0.087772 \leq x \leq 1.646842$
ThermPressInt	real	V	$-0.04 \leq x \leq 5.06$
1Emission	real	$\mu$ A	$5.8812 \leq x \leq 25.6542$

**Table 24: SMD Data File Contents and Structure**

Field Name	Type	Units	Range
3Emission	real	μA	$-0.2022 \leq x \leq 25.5783$
EM1Current	real	μA	$-0.30072 \leq x \leq 38.04108$
EM2Current	real	μA	$7.518 \leq x \leq 38.04108$
CmdsRec	integer		$0 \leq x \leq 65535$
CmdsRej	integer		$0 \leq x \leq 65535$
AlfsRec	integer		$0 \leq x \leq 65535$
AlfsRej	integer		$0 \leq x \leq 65535$
ConfigNum	integer		$0 \leq x \leq 255$
Time1	integer		$0 \leq x \leq 16777215$
CmdSerNo2	integer		$0 \leq x \leq 255$
Time2	integer		$0 \leq x \leq 16777215$
CmdSerNo3	integer		$0 \leq x \leq 255$
Time3	integer		$0 \leq x \leq 16777215$
CRC			n/a

#### 4.3.5 INMS HMD Data Product Formats

The HMD files contain the complete contents of the housekeeping memory dump telemetry packets. As with the SMD the INMS team uses this file to verify the state of the instrument. Table 25 below describes the contents and ranges of the HMD data files. These files contain the contents of the housekeeping memory dump packets, converted to dimensional quantities, where appropriate. Each record consists of 9 header items followed by the contents of the telemetry packet.

**Table 25 :HMD Data File Contents and Structure**

Field Name	Type	Units	Range
OriginalPacketID	integer		
EventID	integer		
PacketID	integer		
SCLKTime	string		
SCLKRaw	real		
ERTTime	string		
Processedtime	string		
Mode	string		
Valid	boolean		
InstMode	integer		0-7
SequenceTable	integer		0-31
CycleIndex	integer		0, 15

<i>Table 25 :HMD Data File Contents and Structure</i>			
<b>Field Name</b>	<b>Type</b>	<b>Units</b>	<b>Range</b>
ScanIndex	integer		0, 15
ElapsedTime	integer	s	0-65535
CycleTable	integer		0-63
Spare	integer		n/a
MemoryType	integer		0-7
NumberOfWords	integer		(1-32)
StartAddress	integer		0-65535
TCReceived	integer		0-255
BIU_Bus_Fault	integer		0-255
Machine_Error	integer		0, 15
TCRejected	integer		0, 15
InstTMMMode	integer		0-255
BIUSpare	integer		0-3
TGORDT	boolean		0, 1
AlfOverrideInhibit	boolean		0, 1
AlfBootEnable	boolean		0-255
DefSciEnable	boolean		0-3
BIUSleep	boolean		0, 1
BIUPORD0	boolean		0, 1
HKFull	boolean		0, 1
HKSSysF	boolean		0, 1
HKMSGError	boolean		0, 1
TMSCErr	boolean		0, 1
StTblError	boolean		0, 1
AncBCErr	boolean		0, 1
BIUSpare2	boolean		0, 1
RTIsFail	boolean		0, 1
Fil1ON	boolean		0, 1
Fil2ON	boolean		0, 1
Fil3ON	boolean		0, 1
Fil4ON	boolean		0, 1
DconSpare1	boolean		0, 1
Fil6ON	boolean		0, 1
DconSpare2	integer		0-3
BIUWDX	boolean		0, 1
BIUFT	boolean		0, 1

<i>Table 25 :HMD Data File Contents and Structure</i>			
<b>Field Name</b>	<b>Type</b>	<b>Units</b>	<b>Range</b>
FCFT	boolean		0, 1
FCTgo	boolean		0, 1
FCllad	boolean		0, 1
FCNPU	boolean		0, 1
FCSuren	boolean		0-3
BIUDTsLoaded	boolean		0, 1
Word0	integer		0 ≤ x ≤ 0xFFFF
·   · ·	· · ·		0 ≤ x ≤ 0xFFFF
Word31	integer		0 ≤ x ≤ 0xFFFF
TgoDetect	boolean		0, 1
BIUResetOcc	boolean		0, 1
ICError	boolean		0, 1
TGOToggle	boolean		0, 1
SubmoduleID	integer		0, 15
TrapFlag	integer		0-3
ModuleID	integer		0-63
CRC			n/a

**APPENDIX A: DIRECTORY STRUCTURE FOR VOLUMES OF THE  
CO-S-INMS-3-L1A-U-V1.0 DATA SET**

```
+--INDEX ----+----INDXINFO.TXT
|              +----INDEX.TAB
|              \---INDEX.LBL
|
+--DOCUMENT---+
|              +----DOCINFO.TXT
|              +----VOLSIS.DOC
|              +----VOLSIS.ASC
|              +----VOLSIS.LBL
|              \---additional documentation files and labels
|
+--CATALOG  --+----CATINFO.TXT
|              +----CO_INMS_L1A_DS.CAT
|              +----CO_INSTHOST.CAT
|              +----CO_INMS_INST.CAT
|              +----CASSINI_MISSION.CAT
|              +----CO_INMS_PERSION.CAT
|              \---CO_INMS_REF.CAT
|
+--CALIB-----+----yyyyddd_CAL_vv.CSV
|              \---yyyyddd_CAL_vv.CSV
|
+--DATA-----+----yyyy-----+----ddd-----+----yyyyddd00_L1A_vv.CSV
|              |              |              +----yyyyddd01_L1A_vv.CSV
|              |              |              +----yyyyddd02_L1A_vv.CSV
|              |              |              +----yyyyddd03_L1A_vv.CSV
|              |              |              +----up to 20 additional L1A files
|              |              |              +----yyyyddd00_L1A_vv.LBL
|              |              |              +----yyyyddd01_L1A_vv.LBL
|              |              |              +----yyyyddd02_L1A_vv.LBL
|              |              |              +----yyyyddd03_L1A_vv.LBL
|              |              |              +----up to 20 additional L1A labels
|              |              |              +----L1A_STRUCT_vv.FMT
|              |              +----ddd-----+
|              \-----yyyy-----+----ddd-----+
|
v
```

*continued on next page*



*continued from previous page*

```
^
|
+-BROWSE-----+----yyyy-----+----ddd-----+----yyyddd00_SPECTRA_vv.PNG
|               |               |               +----yyyddd00_SPECTRA_vv.LBL
|               |               |               +----yyyddd00_LINE_vv.PNG
|               |               |               +----yyyddd00_LINE_vv.LBL
|               |               |               +----up to 5 more browse product sets
|               |               +----ddd-----+
|               \-----yyyy-----+----ddd-----+
|
\--EXTRAS-----+--SOFTWARE--+---INFO.TXT
|               |             +---DISCLAIMER.TXT
|               |             +---INMS_*.PRO   idl v6.1 source code files
|               |             +---SPRL_*.PRO   idl v6.1 source code files
|               |             +---USERGUIDE.DOC user's guide to routines
|               |             \---INMS_ANALYSIS_HELP.HTL online help
|
\--CALREPORT--> see APENDIX C
```

**APPENDIX B: DIRECTORY STRUCTURE FOR VOLUMES OF THE  
 CO-S-INMS-2-PKT-U-V1.0 DATA SET**

```

+-INDEX ----+----INDXINFO.TXT
|           +----INDEX.TAB
|           \----INDEX.LBL
|
+-DOCUMENT--+
|           +----DOCINFO.TXT
|           +----VOLSIS.DOC
|           +----VOLSIS.ASC
|           +----VOLSIS.LBL
|           \--- additional documentation files and labels
|
+-CATALOG  --+----CATINFO.TXT
|           +----CO_INMS_PKT_DS.CAT
|           +----CO_INSTHOST.CAT
|           +----CO_INMS_INST.CAT
|           +----CASSINI_MISSION.CAT
|           +----CO_INMS_PERSION.CAT
|           \----CO_INMS_REF.CAT
|
\--DATA-----+----yyyy---+----ddd-----+----yyyyddd00_SCI_vv.CSV
|              |              |              |
|              |              |              | up to 23 additional SCI files
|              |              |              | +----yyyyddd00_SCI_vv.LBL
|              |              |              | up to 23 additional L1A Labels
|              |              |              | +----yyyyddd00_HKG_vv.CSV
|              |              |              | +----yyyyddd00_OTS_vv.CSV
|              |              |              | +----yyyyddd00_SMD_vv.CSV
|              |              |              | +----yyyyddd00_HMD_vv.CSV
|              |              |              | +----yyyyddd00_SCI_vv.LBL
|              |              |              | +----yyyyddd00_HKG_vv.LBL
|              |              |              | +----yyyyddd00_OTS_vv.LBL
|              |              |              | +----yyyyddd00_SMD_vv.LBL
|              |              |              | +----yyyyddd00_HMD_vv.LBL
|              |              +----ddd-----+
|              +----ddd-----+
\-----yyyy---+----ddd-----+
  
```

## APPENDIX C: CALIBRATION REPORT DIRECTORY STRUCTURE

CALREPORT->

```
+---INMS_FU_Characterization
|
| +---1-Directory
| +---2-General
| |
| | +---2.1-Document_status
| | +---2.2-Data_flow
| | +---2.3-Data_programs
| | +---2.4-Data_program_ouput
| | |
| | | +---2.4.01-0130n2pri
| | | +---2.4.02-0131n2sec
| | | +---2.4.03-0131arsec
| | | +---2.4.04-0201arpri
| | | +---2.4.05-0201ch4sec
| | | +---2.4.06-0202ch4pri
| | | +---2.4.07-0202hepri
| | | +---2.4.08-0202hesec
| | | +---2.4.09-0204h2pri
| | | +---2.4.10-0204h2sec
| | | +---2.4.11-0205krpri
| | | +---2.4.12-0205krsec
| | | +---2.4.13-0208ar02.8ev
| | | +---2.4.14-0209ar08.0ev
| | | +---2.4.15-0209ar14.0ev
| | | +---2.4.16-0210kr02.8ev
| | | +---2.4.17-0210kr08.0ev
| | | +---2.4.18-0210kr14.0ev
| | | +---2.4.19-0211he02.8ev
| | | +---2.4.20-0213c2h2sec
| | | +---2.4.21-0213c2h2pri
| | | +---2.4.22-0213c2h4pri
| | | +---2.4.23-0213c2h4sec
| | | \---2.4.24-0213noble
| | \---2.5-Miscellaneous_files
| +---3-GSE_files
| |
| | +---3.1-ATOL_sequences
| | +---3.2-ATOL_serial_numbers
| | +---3.3-SUN_files
| | |
| | | +---3.3.4-GSE_data_therm_ion
| | | \---3.3.5-GSE_phd_summary
| | +---3.4-Programs
| | |
| | | +---3.4.1-avghk
| | | \---3.4.2-avgscience_sp1
| | \---3.5-Misc_files
| | |
| | | +---3.5.1-Commands
| | | |
| | | | \---Commands
| | | | |
| | | | | +---bak
| | | | | \---tmp
| | | \---3.5.2-Scripts
| | | |
| | | | \---Scripts
```

v v

*continued on next page*



*continued from previous page*

```
^      ^      ^      ^
|      |      |      |
|      |      |      |      +---0205krsec_r3
|      |      |      |      +---0213c2h2pri_r3
|      |      |      |      +---0213c2h2sec_r3
|      |      |      |      +---0213c2h4pri_r3
|      |      |      |      +---0213c2h4sec_r3
|      |      |      |      \---FU_Thermal_Summary_r3
|      |      |      |      +---FU_description_r3
|      |      |      |      \---FU_files_r3
|      |      |      |      \---5.2.2-Other
|      |      |      |      +---5.2.2.1-N2_tracking
|      |      |      |      |      +---5.2.2.1.1-N2_tracking_descript
|      |      |      |      |      +---5.2.2.1.2-N2_tracking_data
|      |      |      |      |      +---5.2.2.1.3-N2_tracking_GSE_files
|      |      |      |      |      \---5.2.2.1.4-N2_tracking_plots
|      |      |      |      +---5.2.2.2-SRG_Baratron
|      |      |      |      +---5.2.2.3-Sensitivity_summary
|      |      |      |      \---5.2.2.4-Noble_gas_scan
|      |      |      |      \---5.2.2.4.2-noble_plots
|      |      |      |      \---6-Miscellaneous
|      |      |      |      +---6.1-Ion_defl_V
|      |      |      |      |      \---6.1.2-defl_dac_plots
|      |      |      |      +---6.2-INMS_volts
|      |      |      |      +---6.3-Chacterization_system
|      |      |      |      |      +---6.3.1-system_description
|      |      |      |      |      +---6.3.2-procedures
|      |      |      |      |      |      \---6.3.2.2-Therm_gas_inlet_dia
|      |      |      |      |      \---6.3.3-system_pictures
|      |      |      |      +---6.4-SEM_gain
|      |      |      |      |      +---6.4.2-SEM_gain_data
|      |      |      |      |      +---6.4.2.1_SEM_gain_descript
|      |      |      |      |      \---6.4.3-Sem_gain_plots
|      |      |      |      +---6.5-Open_source_quad_bias
|      |      |      |      +---6.6-INMS_trend_analysis
|      |      |      |      \---6.7-INMS_sensor
|      |      |      |      +---6.7.1-sensor_schematic
|      |      |      |      \---6.7.2-sensor_on_char_sys
|
v
```

*continued on next page*

*continued from previous page*

```
^
|
| \---INMS_EU_Characterization
| | +---General
| | +---Ions
| | | +---Argon_Ions
| | | | +---1998-0917-ArgonIons10V
| | | | +---1998-0917-ArgonIons13_5V
| | | | +---1998-0917-ArgonIons20V
| | | | \---1998-0917-ArgonIons6_5V
| | | +---Helium_Ions
| | | | +---1998-0916-HeliumIons10V
| | | | +---1998-0916-HeliumIons13_5V
| | | | +---1998-0916-HeliumIons20V
| | | | \---1998-0916-HeliumIons6_5V
| | | +---Hydrogen_Ions
| | | | +---1998-0917_HydrogenIons13_5V
| | | | +---1998-0917_HydrogenIons10V
| | | | +---1998-0917_HydrogenIons20V
| | | | \---1998-0917_HydrogenIons6_5V
| | | +---KryptonIons
| | | | +---1998-0918-KryptonIons10V
| | | | +---1998-0918-KryptonIons13_5V
| | | | +---1998-0918-KryptonIons20V
| | | | \---1998-0918-KryptonIons6_5V
| | | +---Neon_Ions
| | | | +---1998-0918-NeonIons10V
| | | | +---1998-0918-NeonIons13_5V
| | | | +---1998-0918-NeonIons20V
| | | | \---1998-0918-NeonIons6_5V
| | | +---Nitrogen_Ions
| | | | +---1998-0910-NitrogenIons20V
| | | | +---1998-0911-NitrogenIons13_5V
| | | | +---1998-0914-NitrogenIons10V
| | | | +---1998-0915-NitrogenIons6_5V
| | | | \---1998-0928-NitrogenIons6_5V
| | | +---Switching Lens
| | | \---X_Ion_Summary
| | | | +---EU_FU_6_5ev_Compare
| | | | | \---ion_fit
| | | | | | +---10ev_L1_30v
| | | | | | +---13_5ev_L1_30v
| | | | | | +---20ev_L1_30v
| | | | | | \---6.5ev_L1_30v
| | |
| |
| v
v
```

*continued on next page*

*continued from previous page*

```
^      ^
|      |
|      | +---Neutral Beam
|      | | +---1998-0919_NeutralBeamTest
|      | | +---1998-0921-MoreBeaming
|      | | +---1998-0922-NeutralBeamArKrInH2
|      | | \---X_Neutral_Beam_Summary.xls
|      | +---Nitrogen_Tracking
|      | +---Thermal_Gas
|      | | +---Acetylene
|      | | | \---1998-0720-AcetyleneCal
|      | | +---Argon
|      | | | \---1998-0629-Argon
|      | | +---Argon in Helium
|      | | | \---1998-0824-ArgonInHelium
|      | | +---Benzene
|      | | | \---1998-1001-Benzene
|      | | +---Carbon Dioxide
|      | | | \---1998-0729-CarbonDioxideCal
|      | | +---Carbon Monoxide in Helium
|      | | | +---1998-0723-COinHelium
|      | | | \---1998-0819-COinHelium
|      | | +---CarbonMonoxide
|      | | | \---1998-0925-ThermalCO
|      | | +---Ethane
|      | | | \---1998-0723-EthaneCal
|      | | +---Ethylene
|      | | | \---1998-0722-EthyleneCal
|      | | +---Helium
|      | | | \---1998-0715-Helium
|      | | +---Hydrogen
|      | | | \---1998-0716-HydrogenCal
|      | | +---HydrogenCyanide in Helium
|      | | | +---1998-0930-HCNinHelium_run_1
|      | | | \---1998-0930-HCNinHelium_run_2
|      | | +---Krypton
|      | | | \---1998-0716-KryptonCal
|      | | +---Methane
|      | | | \---1998-0629_Methane
|      | | +---Methylacetylene (Propyne) in Helium
|      | | | +---1998-0824-MethylacetyleneInHelium_run_1
|      | | | \---1998-0824-MethylacetyleneInHelium_run_2
|      | | +---Neon
|      | | | \---1998-0717-NeonCal
|      | | +---Nitrogen
|      | | | \---1998-0629-Nitrogen
|      |
|      v
```

*continued on next page*

*continued from previous page*

```
/ ^
| |
| | +---Oxygen
| | | +---1998-0727-OxygenCal
| | | \---1998-0728-OxygenCal
| | +---Propadiene (Allene) in Helium
| | | +---1998-0820-PropadieneInHelium
| | | \---1998-0821-PropadieneInHelium
| | +---Propane
| | | \---1998-0717-Propane
| | \---X_Thermal_Summary
| | | \---EU_FU_Thermal_Summary
| | | | +---EU_save
| | | | +---FU_description_r3
| | | | +---FU_save
| | | | \---V _Anicich_Communications
| | \---Miscellaneous
|
+---Other
```



**APPENDIX D: L1A STRUCTURE FILE CONTENTS**

OBJECT = FIELD  
 FIELD\_NUMBER = 1  
 BYTES = 21  
 DATA\_TYPE = TIME  
 NAME = "SCLK"  
 FORMAT = "A21"  
 DESCRIPTION = "Spacecraft  
 event time in the UTC time  
 scale expressed as a PDS  
 compliant date-time  
 string."  
 END\_OBJECT = FIELD

OBJECT = FIELD  
 FIELD\_NUMBER = 2  
 BYTES = 8  
 DATA\_TYPE = ASCII\_INTEGER  
 NAME = "UTTIME"  
 FORMAT = "I8"  
 DESCRIPTION = "Time of  
 measurement expressed in  
 msec since midnight UTC."  
 UNIT = "ms"  
 VALID\_MINIMUM = 0  
 VALID\_MAXIMUM = 86400001  
 END\_OBJECT = FIELD

OBJECT = FIELD  
 FIELD\_NUMBER = 3  
 BYTES = 26  
 DATA\_TYPE = CHARACTER  
 FORMAT = "A26"  
 NAME = "TARGET"  
 DESCRIPTION = "Name of  
 target body."  
 END\_OBJECT = FIELD

OBJECT = FIELD  
 FIELD\_NUMBER = 4  
 BYTES = 8  
 DATA\_TYPE = ASCII\_INTEGER  
 NAME = "TIME\_CA"  
 FORMAT = "I8"  
 DESCRIPTION = "Time since  
 closest approach."  
 UNIT = "ms"  
 VALID\_MINIMUM = -86400000  
 VALID\_MAXIMUM = 86400000  
 END\_OBJECT = FIELD

OBJECT = FIELD  
 FIELD\_NUMBER = 5  
 BYTES = 9  
 DATA\_TYPE = ASCII\_REAL  
 NAME = "TARG\_POS\_X"  
 FORMAT = "F9.0"  
 DESCRIPTION = "X component  
 of the target body position  
 in the IAU Saturn reference  
 frame, included within 1  
 hour of closest approach."  
 UNIT = "km"  
 VALID\_MINIMUM = -1.0E07  
 VALID\_MAXIMUM = 1.0E07  
 END\_OBJECT = FIELD

OBJECT = FIELD  
 FIELD\_NUMBER = 6  
 BYTES = 9  
 DATA\_TYPE = ASCII\_REAL  
 NAME = "TARG\_POS\_Y"  
 FORMAT = "F9.0"  
 DESCRIPTION = "Y component  
 of the target body position  
 in the IAU Saturn reference  
 frame, included within 1  
 hour of closest approach."  
 UNIT = "km"  
 VALID\_MINIMUM = -1.0E07  
 VALID\_MAXIMUM = 1.0E07  
 END\_OBJECT = FIELD

OBJECT = FIELD  
 FIELD\_NUMBER = 7  
 BYTES = 9  
 DATA\_TYPE = ASCII\_REAL  
 NAME = "TARG\_POS\_Z"  
 FORMAT = "F9.0"  
 DESCRIPTION = "Z component  
 of the target body position  
 in the IAU Saturn reference  
 frame, included within 1  
 hour of closest approach."  
 UNIT = "km"  
 VALID\_MINIMUM = -1.0E07  
 VALID\_MAXIMUM = 1.0E07  
 END\_OBJECT = FIELD

```

OBJECT      = FIELD
FIELD_NUMBER = 8
BYTES      = 4
DATA_TYPE  = CHARACTER
NAME       = "SOURCE"
FORMAT     = "A4"
DESCRIPTION = "Ion source
              used for this measurement,
              Open Source Ion (osi)
              Closed Source Neutral(csn)
              Open Source Neutral Beam
              (osnb)
              Open Souce Neutral Thermal
              (osnt)"
END_OBJECT  = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 9
BYTES      = 4
DATA_TYPE  = ASCII_INTEGER
NAME       =
           "DATA_RELIABILITY"
FORMAT     = "I4"
DESCRIPTION = "This value is
              set to a non-zero value
              during scans in which an
              instrument transition may
              cause data reliability
              concerns. (Not implemented
              in Version 05 data files)"
END_OBJECT  = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 10
BYTES      = 8
DATA_TYPE  = CHARACTER
NAME       = "TABLE_SET_ID"
FORMAT     = "A8"
DESCRIPTION = "Table set
              Identifier, consisting of
              an ID and revision number,
              TTTT-rrrr."
END_OBJECT  = FIELD

```

```

OBJECT      = FIELD
FIELD_NUMBER = 11
BYTES      = 3
DATA_TYPE  = ASCII_INTEGER
NAME       = "COADD_CNT"
FORMAT     = "I3"
DESCRIPTION = "Specifies the
              number of integration
              periods added together. A
              value of 1 indicates no
              coadding, 255 indicates
              maximum coadding - minimum
              data rate."
VALID_MINIMUM = 1
VALID_MAXIMUM = 255
END_OBJECT  = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 12
BYTES      = 7
DATA_TYPE  = CHARACTER
NAME       =
           "OSP_FIL_1_STATUS"
FORMAT     = "A7"
DESCRIPTION = "Open source
              primary filament status
              (fil_1), OFF, LOW-EV (25eV)
              HIGH-EV (70eV)"
END_OBJECT  = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 13
BYTES      = 7
DATA_TYPE  = CHARACTER
NAME       =
           "OSS_FIL_2_STATUS"
FORMAT     = "A7"
DESCRIPTION = "Open source
              secondary filament status
              (fil_2), OFF, LOW-EV (25eV)
              HIGH-EV (70eV)"
END_OBJECT  = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 14
BYTES      = 7
DATA_TYPE  = CHARACTER
NAME       =
           "CSP_FIL_3_STATUS"
FORMAT     = "A7"
DESCRIPTION = "Closed source
              primary filament (fil_3)
              status, OFF, LOW-EV (27eV)
              HIGH-EV (71eV)"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT  = FIELD

```

```

OBJECT      = FIELD
FIELD_NUMBER = 15
BYTES      = 7
DATA_TYPE  = CHARACTER
NAME       =
  "CSS_FIL_4_STATUS"
FORMAT    = "A7"
DESCRIPTION = "Closed source
  secondary filament (fil_4)
  status, OFF, LOW-EV (27eV)
  HIGH-EV(71eV)"
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 16
BYTES      = 2
DATA_TYPE  = ASCII_INTEGER
NAME       = "SEQ_TABLE"
DESCRIPTION = "Number of the
  sequence table controlling
  the instrument operation.
  This table lists a set of
  cycle tables, each one of
  which specifies one or more
  mass scans."
VALID_MINIMUM = 1
VALID_MAXIMUM = 64
END_OBJECT   = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 17
BYTES      = 2
DATA_TYPE  = ASCII_INTEGER
NAME       = "CYC_NUM"
FORMAT    = "I2"
DESCRIPTION = "The number of
  the cycle within the
  sequence, indexes in this
  sequence table."
VALID_MINIMUM = 1
VALID_MAXIMUM = 31
END_OBJECT   = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 18
BYTES      = 2
DATA_TYPE  = ASCII_INTEGER
NAME       = "CYC_TABLE"
FORMAT    = "I2"
DESCRIPTION =
  "Identification number of
  the cycle table controlling
  the current mass scan. This
  table selects the mass,
  focus, trap, switching and
  D/A table used to operate
  
```

```

  the instrument for mass
  scan."
VALID_MINIMUM = 1
VALID_MAXIMUM = 64
END_OBJECT   = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 19
BYTES      = 2
DATA_TYPE  = ASCII_INTEGER
NAME       = "SCAN_NUM"
DESCRIPTION = "The number of
  the scan within the cycle,
  indexes the cycle table."
VALID_MINIMUM = 1
VALID_MAXIMUM = 31
END_OBJECT   = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 20
BYTES      = 2
DATA_TYPE  = ASCII_INTEGER
NAME       = "TRAP_TABLE"
FORMAT    = "I2"
DESCRIPTION =
  "Identification number of
  the trap table specifying
  collimator, deflector, top
  plate and OL4 voltages
  used in the mass scan."
VALID_MINIMUM = 1
VALID_MAXIMUM = 31
END_OBJECT   = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 21
BYTES      = 2
DATA_TYPE  = ASCII_INTEGER
NAME       = "SW_TABLE"
FORMAT    = "I2"
DESCRIPTION =
  "Identification number of
  the Switching table
  specifying the quadrupole
  rod voltages."
VALID_MINIMUM = 1
VALID_MAXIMUM = 31
END_OBJECT   = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 22
BYTES      = 2
DATA_TYPE  = ASCII_INTEGER
NAME       = "MASS_TABLE"
FORMAT     = "I2"
DESCRIPTION =
  "Identification number of
  the mass table specifying
  the 68 mass/charge values
  making up a mass scan."
VALID_MINIMUM = 1
VALID_MAXIMUM = 96
END_OBJECT   = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 23
BYTES      = 2
DATA_TYPE  = ASCII_INTEGER
NAME       = "FOCUS_TABLE"
FORMAT     = "I2"
DESCRIPTION =
  "Identification number of
  the focus table specifying
  OL1, OL2, OL3, endplate,
  ion lens, and quadrupole
  bias voltages."
VALID_MINIMUM = 1
VALID_MAXIMUM = 31
END_OBJECT   = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 24
BYTES      = 2
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I2"
NAME       = "DA_TABLE"
DESCRIPTION =
  "Identification number of
  the D/A table specifying
  the electron multiplier and
  detector threshold
  settings."
VALID_MINIMUM = 1
VALID_MAXIMUM = 16
END_OBJECT   = FIELD

```

```

OBJECT      = FIELD
FIELD_NUMBER = 25
BYTES      = 6
DATA_TYPE  = ASCII_REAL
NAME       =
  "VELOCITY_COMP"
FORMAT     = "F6.3"
DESCRIPTION = "Compensation
  velocity used in onboard
  computation of lens and
  deflector voltages"
UNIT       = "km/s"
VALID_MINIMUM = 0
VALID_MAXIMUM = 50.0
END_OBJECT   = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 26
BYTES      = 2
DATA_TYPE  = ASCII_INTEGER
NAME       = "IPNUM"
FORMAT     = "I2"
DESCRIPTION = "Integration
  period number, indexes the
  mass, trap switching and
  focus tables."
VALID_MINIMUM = 1
VALID_MAXIMUM = 68
END_OBJECT   = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 27
BYTES      = 6
DATA_TYPE  = ASCII_REAL
NAME       = "MASS"
FORMAT     = "F6.3"
DESCRIPTION = "Mass per unit
  charge detected during
  current integration period"
UNIT       = "AMU/Z"
VALID_MINIMUM = 0.125
VALID_MAXIMUM = 99.0
END_OBJECT   = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 28
BYTES      = 6
DATA_TYPE  = ASCII_REAL
NAME       = "OS_LENS2"
FORMAT     = "F6.2"
DESCRIPTION = "Open source
  lens 2 voltage."
UNIT       = "v"
VALID_MINIMUM = -10.00
VALID_MAXIMUM = 10.00
END_OBJECT   = FIELD

```

```
OBJECT      = FIELD
FIELD_NUMBER = 29
BYTES      = 6
DATA_TYPE  = ASCII_REAL
NAME       = "OS_LENS1"
FORMAT     = "F6.2"
DESCRIPTION = "Open source
             lens 1 voltage."
UNIT       = "v"
VALID_MINIMUM = -10.00
VALID_MAXIMUM = 10.00
END_OBJECT  = FIELD
```

```
OBJECT      = FIELD
FIELD_NUMBER = 30
BYTES      = 6
DATA_TYPE  = ASCII_REAL
NAME       = "OS_LENS4"
FORMAT     = "F6.2"
DESCRIPTION = "Open source
             lens 4 voltage."
UNIT       = "v"
VALID_MINIMUM = -10.00
VALID_MAXIMUM = 10.00
END_OBJECT  = FIELD
```

```
OBJECT      = FIELD
FIELD_NUMBER = 31
BYTES      = 6
DATA_TYPE  = ASCII_REAL
NAME       = "OS_LENS3"
FORMAT     = "F6.2"
DESCRIPTION = "Open source
             lens 3 voltage."
UNIT       = "v"
VALID_MINIMUM = -10.00
VALID_MAXIMUM = 10.00
END_OBJECT  = FIELD
```

```
OBJECT      = FIELD
FIELD_NUMBER = 32
BYTES      = 7
DATA_TYPE  = ASCII_REAL
NAME       = "QP_LENS2"
FORMAT     = "F7.3"
DESCRIPTION = "Quadrapole
             lens 2 voltage."
UNIT       = "v"
VALID_MINIMUM = -200.0
VALID_MAXIMUM = 200.0
END_OBJECT  = FIELD
```

```
OBJECT      = FIELD
FIELD_NUMBER = 33
BYTES      = 7
DATA_TYPE  = ASCII_REAL
NAME       = "QP_LENS1"
FORMAT     = "F7.3"
DESCRIPTION = "Quadrapole
             lens 1 voltage."
UNIT       = "v"
VALID_MINIMUM = -200.0
VALID_MAXIMUM = 200.0
END_OBJECT  = FIELD
```

```
OBJECT      = FIELD
FIELD_NUMBER = 34
BYTES      = 7
DATA_TYPE  = ASCII_REAL
NAME       = "QP_LENS4"
FORMAT     = "F7.3"
DESCRIPTION = "Quadrapole
             lens 4 voltage."
UNIT       = "v"
VALID_MINIMUM = -200.0
VALID_MAXIMUM = 200.0
END_OBJECT  = FIELD
```

```
OBJECT      = FIELD
FIELD_NUMBER = 35
BYTES      = 7
DATA_TYPE  = ASCII_REAL
NAME       = "QP_LENS3"
FORMAT     = "F7.3"
DESCRIPTION = "Quadrapole
             lens 3 voltage."
UNIT       = "v"
VALID_MINIMUM = -200.0
VALID_MAXIMUM = 200.0
END_OBJECT  = FIELD
```

```
OBJECT      = FIELD
FIELD_NUMBER = 36
BYTES      = 7
DATA_TYPE  = ASCII_REAL
NAME       = "QP_BIAS"
DESCRIPTION = "Quadrapole
             bias voltage."
FORMAT     = "F7.3"
UNIT       = "v"
VALID_MINIMUM = -200.0
VALID_MAXIMUM = 200.0
END_OBJECT  = FIELD
```

```

OBJECT      = FIELD
FIELD_NUMBER = 37
BYTES      = 6
DATA_TYPE  = ASCII_REAL
NAME       = "ION_DEFL2"
FORMAT     = "6.2"
DESCRIPTION = "Ion deflector
  2 voltage."
UNIT       = "v"
VALID_MINIMUM = -62.0
VALID_MAXIMUM = 62.0
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 38
BYTES      = 6
DATA_TYPE  = ASCII_REAL
NAME       = "ION_DEFL1"
FORMAT     = "6.2"
DESCRIPTION = "Ion deflector
  1 voltage."
UNIT       = "v"
VALID_MINIMUM = -62.0
VALID_MAXIMUM = 62.0
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 39
BYTES      = 6
DATA_TYPE  = ASCII_REAL
NAME       = "ION_DEFL4"
FORMAT     = "F6.2"
DESCRIPTION = "Ion deflector
  4 voltage."
UNIT       = "v"
VALID_MINIMUM = -62.0
VALID_MAXIMUM = 62.0
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 40
BYTES      = 6
DATA_TYPE  = ASCII_REAL
NAME       = "ION_DEFL3"
DESCRIPTION = "Ion deflector
  3 voltage."
FORMAT     = "F6.2"
UNIT       = "v"
VALID_MINIMUM = -62.0
VALID_MAXIMUM = 62.0
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 41
BYTES      = 6
DATA_TYPE  = ASCII_REAL
NAME       = "TOP_PLATE"
FORMAT     = "F6.2"
DESCRIPTION = "Top plate
  lens voltage."
UNIT       = "v"
VALID_MINIMUM = -30.0
VALID_MAXIMUM = 30.0
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 42
BYTES      = 7
DATA_TYPE  = ASCII_REAL
NAME       = "P_ENERGY"
FORMAT     = "F7.3"
DESCRIPTION = "Particle
  Energy."
UNIT       = "ev"
VALID_MINIMUM = 0.
VALID_MAXIMUM = 50.
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 43
BYTES      = 9
DATA_TYPE  = ASCII_REAL
NAME       = "ALT_T"
FORMAT     = "F9.2"
DESCRIPTION = "Altitude of
  the spacecraft above the
  surface of the named target
  body, included within 1
  hour of closest approach"
UNIT       = "km"
VALID_MINIMUM = -1.0E05
VALID_MAXIMUM = 1.0E05
END_OBJECT = FIELD
  
```

OBJECT = FIELD  
 FIELD\_NUMBER = 44  
 BYTES = 9  
 DATA\_TYPE = ASCII\_REAL  
 NAME = "VIEW\_DIR\_T\_X"  
 FORMAT = "F9.6"  
 DESCRIPTION = "Components of  
 the UNIT vector in the  
 direction of the INMS  
 aperture outward normal  
 expressed in the target  
 centered IAU coordinate  
 frame, included within 1  
 hour of closest approach."  
 VALID\_MINIMUM = -1.0  
 VALID\_MAXIMUM = 1.0  
 END\_OBJECT = FIELD

OBJECT = FIELD  
 FIELD\_NUMBER = 45  
 BYTES = 9  
 DATA\_TYPE = ASCII\_REAL  
 NAME = "VIEW\_DIR\_T\_Y"  
 FORMAT = "F9.6"  
 DESCRIPTION = "Components of  
 the UNIT vector in the  
 direction of the INMS  
 aperture outward normal  
 expressed in the target  
 centered IAU coordinate  
 frame, included within 1  
 hour of closest approach."  
 VALID\_MINIMUM = -1.0  
 VALID\_MAXIMUM = 1.0  
 END\_OBJECT = FIELD

OBJECT = FIELD  
 FIELD\_NUMBER = 46  
 BYTES = 9  
 DATA\_TYPE = ASCII\_REAL  
 FORMAT = "F9.6"  
 NAME = "VIEW\_DIR\_T\_Z"  
 DESCRIPTION = "Components of  
 the UNIT vector in the  
 direction of the INMS  
 aperture outward normal  
 expressed in the target  
 centered IAU coordinate  
 frame, included within 1  
 hour of closest approach."  
 VALID\_MINIMUM = -1.0  
 VALID\_MAXIMUM = 1.0  
 END\_OBJECT = FIELD

OBJECT = FIELD  
 FIELD\_NUMBER = 47  
 BYTES = 9  
 DATA\_TYPE = ASCII\_REAL  
 NAME = "SC\_POS\_T\_X"  
 FORMAT = "F9.2"  
 DESCRIPTION = "X-component  
 of spacecraft position with  
 respect to the named target  
 in the target centered IAU  
 coordinate frame, included  
 within 1 hour of closest  
 approach."  
 UNIT = "km"  
 VALID\_MINIMUM = -1.0E05  
 VALID\_MAXIMUM = 1.0E05  
 END\_OBJECT = FIELD

OBJECT = FIELD  
 FIELD\_NUMBER = 48  
 BYTES = 9  
 DATA\_TYPE = ASCII\_REAL  
 NAME = "SC\_POS\_T\_Y"  
 FORMAT = "F9.2"  
 DESCRIPTION = "Y-component  
 of spacecraft position with  
 respect to the named target  
 in the target centered IAU  
 coordinate frame, included  
 within 1 hour of closest  
 approach."  
 UNIT = "km"  
 VALID\_MINIMUM = -1.0E05  
 VALID\_MAXIMUM = 1.0E05  
 END\_OBJECT = FIELD

OBJECT = FIELD  
 FIELD\_NUMBER = 49  
 BYTES = 9  
 DATA\_TYPE = ASCII\_REAL  
 NAME = "SC\_POS\_T\_Z"  
 FORMAT = "F9.2"  
 DESCRIPTION = "Z-component  
 of spacecraft position with  
 respect to the named target  
 in the target centered IAU  
 coordinate frame, included  
 within 1 hour of closest  
 approach."  
 UNIT = "km"  
 VALID\_MINIMUM = -1.0E05  
 VALID\_MAXIMUM = 1.0E05  
 END\_OBJECT = FIELD

```
OBJECT      = FIELD
FIELD_NUMBER = 50
BYTES       = 7
DATA_TYPE  = ASCII_REAL
NAME       = "SC_VEL_T_X"
FORMAT     = "F7.3"
DESCRIPTION = "X-component
of spacecraft velocity with
respect to the named target
in the target centered IAU
coordinate frame, included
within 1 hour of closest
approach."
UNIT       = "km/s"
VALID_MINIMUM = -100.
VALID_MAXIMUM = 100.
END_OBJECT = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 51
BYTES       = 7
DATA_TYPE  = ASCII_REAL
NAME       = "SC_VEL_T_Y"
FORMAT     = "F7.3"
DESCRIPTION = "Y-component
of spacecraft velocity with
respect to the named target
in the target centered IAU
coordinate frame, included
within 1 hour of closest
approach."
UNIT       = "km/s"
VALID_MINIMUM = -100.
VALID_MAXIMUM = 100.
END_OBJECT = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 52
BYTES       = 7
DATA_TYPE  = ASCII_REAL
NAME       = "SC_VEL_T_Z"
FORMAT     = "F7.3"
DESCRIPTION = "Z-component
of spacecraft velocity with
respect to the named target
in the target centered IAU
coordinate frame, included
within 1 hour of closest
approach."
UNIT       = "km/s"
VALID_MINIMUM = -100.
VALID_MAXIMUM = 100.
END_OBJECT = FIELD
```

```
OBJECT      = FIELD
FIELD_NUMBER = 53
BYTES       = 7
DATA_TYPE  = ASCII_REAL
NAME       = "SC_VEL_T_SCX"
FORMAT     = "F7.3"
DESCRIPTION = "X-component
of spacecraft velocity with
respect to the named target
in the spacecraft centered
coordinate frame, included
within 1 hour of closest
approach."
UNIT       = "km/s"
END_OBJECT = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 54
BYTES       = 7
DATA_TYPE  = ASCII_REAL
NAME       = "SC_VEL_T_SCY"
FORMAT     = "F7.3"
DESCRIPTION = "Y-component
of spacecraft velocity with
respect to the named target
in the spacecraft centered
coordinate frame, included
within 1 hour of closest
approach"
UNIT       = "km/s"
VALID_MINIMUM = -100.
VALID_MAXIMUM = 100.
END_OBJECT = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 55
BYTES       = 7
DATA_TYPE  = ASCII_REAL
NAME       = "SC_VEL_T_SCZ"
FORMAT     = "F7.3"
DESCRIPTION = "Z-component
of spacecraft velocity with
respect to the named target
in the spacecraft centered
coordinate frame, included
within 1 hour of closest
approach"
UNIT       = "km/s"
VALID_MINIMUM = -100.
VALID_MAXIMUM = 100.
END_OBJECT = FIELD
```



```

OBJECT      = FIELD
  FIELD_NUMBER = 56
  BYTES       = 6
  DATA_TYPE  = ASCII_REAL
  NAME        = "LST_T"
  FORMAT      = "F6.3"
  DESCRIPTION = "The local
                solartime at the sub-
                spacecraft point on the
                target body, included
                within 1 hour of closest
                approach."
  UNIT        = "hr"
  VALID_MINIMUM = 0.
  VALID_MAXIMUM = 24.00
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 57
  BYTES       = 7
  DATA_TYPE  = ASCII_REAL
  NAME        = "SZA_T"
  FORMAT      = "F7.3"
  DESCRIPTION = "The solar
                zenith angle at the sub-
                satellite point on the
                target body, included
                within 1 hour of closest
                approach"
  UNIT        = "deg"
  VALID_MINIMUM = 0.
  VALID_MAXIMUM = 180.
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 58
  BYTES       = 6
  DATA_TYPE  = ASCII_REAL
  NAME        = "SS_LONG_T"
  FORMAT      = "F6.2"
  DESCRIPTION = "The west
                longitude of the sub-solar
                point on the target body,
                included within 1 hour of
                closest approach"
  UNIT        = "deg"
  VALID_MINIMUM = 0.
  VALID_MAXIMUM = 360.
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 59
  BYTES       = 9
  DATA_TYPE  = ASCII_REAL
  NAME        = "DISTANCE_S"
  FORMAT      = "F9.0"
  DESCRIPTION = "Distance of
                the spacecraft from
                Saturn's center"
  UNIT        = "km"
  VALID_MINIMUM = -1.0E07
  VALID_MAXIMUM = 1.0E07
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 60
  BYTES       = 9
  DATA_TYPE  = ASCII_REAL
  NAME        = "VIEW_DIR_S_X"
  FORMAT      = "F9.6"
  DESCRIPTION = "Components of
                the UNIT vector in the
                direction of the INMS
                aperture outward normal in
                the Saturn centered IAU
                coordinate frame."
  VALID_MINIMUM = -1.0
  VALID_MAXIMUM = 1.0
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 61
  BYTES       = 9
  DATA_TYPE  = ASCII_REAL
  NAME        = "VIEW_DIR_S_Y"
  FORMAT      = "F9.6"
  DESCRIPTION = "Components of
                the UNIT vector in the
                direction of the INMS
                aperture outward normal in
                the Saturn centered IAU
                coordinate frame."
  VALID_MINIMUM = -1.0
  VALID_MAXIMUM = 1.0
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 62
  BYTES       = 9
  DATA_TYPE  = ASCII_REAL
  NAME        = "VIEW_DIR_S_Z"
  FORMAT      = "F9.6"
  DESCRIPTION = "Components of
                the UNIT vector in the
                direction of the INMS
                aperture outward normal in
  
```

```

    the Saturn centered IAU
    coordinate frame."
    VALID_MINIMUM = -1.0
    VALID_MAXIMUM = 1.0
  END_OBJECT = FIELD

  OBJECT = FIELD
  FIELD_NUMBER = 63
  BYTES = 9
  DATA_TYPE = ASCII_REAL
  NAME = "SC_POS_S_X"
  FORMAT = "F9.0"
  DESCRIPTION = "X-component
    of spacecraft position in
    the Saturn centered IAU
    coordinate frame."
  UNIT = "km"
  VALID_MINIMUM = -1.0E07
  VALID_MAXIMUM = 1.0E07
  END_OBJECT = FIELD

  OBJECT = FIELD
  FIELD_NUMBER = 64
  BYTES = 9
  DATA_TYPE = ASCII_REAL
  NAME = "SC_POS_S_Y"
  FORMAT = "F9.0"
  DESCRIPTION = "Y-component
    of spacecraft position in
    the Saturn centered IAU
    coordinate frame."
  UNIT = "km"
  VALID_MINIMUM = -1.0E07
  VALID_MAXIMUM = 1.0E07
  END_OBJECT = FIELD
  
```

```

  OBJECT = FIELD
  FIELD_NUMBER = 65
  BYTES = 9
  DATA_TYPE = ASCII_REAL
  NAME = "SC_POS_S_Z"
  FORMAT = "F9.0"
  DESCRIPTION = "Z-component
    of spacecraft position in
    the Saturn centered IAU
    coordinate frame."
  UNIT = "km"
  VALID_MINIMUM = -1.0E07
  VALID_MAXIMUM = 1.0E07
  END_OBJECT = FIELD

  OBJECT = FIELD
  FIELD_NUMBER = 66
  BYTES = 7
  DATA_TYPE = ASCII_REAL
  NAME = "SC_VEL_S_X"
  FORMAT = "F7.3"
  DESCRIPTION = "X-component
    of spacecraft velocity in
    the Saturn centered IAU
    coordinate frame."
  UNIT = "km/s"
  VALID_MINIMUM = -100.
  VALID_MAXIMUM = 100.
  END_OBJECT = FIELD

  OBJECT = FIELD
  FIELD_NUMBER = 67
  BYTES = 7
  DATA_TYPE = ASCII_REAL
  NAME = "SC_VEL_S_Y"
  FORMAT = "F7.3"
  DESCRIPTION = "Y-component
    of spacecraft velocity in
    the Saturn centered IAU
    coordinate frame."
  UNIT = "km/s"
  VALID_MINIMUM = -100.
  VALID_MAXIMUM = 100.
  END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 68
BYTES      = 7
DATA_TYPE  = ASCII_REAL
NAME       = "SC_VEL_S_Z"
FORMAT     = "F7.3"
DESCRIPTION = "Z-component
              of spacecraft velocity in
              the Saturn centered IAU
              coordinate frame."
UNIT       = "km/s"
VALID_MINIMUM = -100.
VALID_MAXIMUM = 100.
END_OBJECT  = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 69
BYTES      = 6
DATA_TYPE  = ASCII_REAL
NAME       = "LST_S"
FORMAT     = "F6.3"
DESCRIPTION = "The local
              solar time at the sub-
              spacecraft point on Saturn"
UNIT       = "hr"
VALID_MINIMUM = 0.
VALID_MAXIMUM = 24.00
END_OBJECT  = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 70
BYTES      = 7
DATA_TYPE  = ASCII_REAL
NAME       = "SZA_S"
FORMAT     = "F7.3"
DESCRIPTION = "The solar
              zenith angle at the sub-
              satellite point on Saturn"
UNIT       = "deg"
VALID_MINIMUM = 0.
VALID_MAXIMUM = 180.
END_OBJECT  = FIELD

```

```

OBJECT      = FIELD
FIELD_NUMBER = 71
BYTES      = 6
DATA_TYPE  = ASCII_REAL
NAME       = "SS_LONG_S"
FORMAT     = "F6.2"
DESCRIPTION = "The west
              longitude of the sub-solar
              point on Saturn"
UNIT       = "deg"
VALID_MINIMUM = 0.
VALID_MAXIMUM = 360.
END_OBJECT  = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 72
BYTES      = 9
DATA_TYPE  = ASCII_REAL
NAME       =
              "SC_ATT_ANGLE_RA"
FORMAT     = "F9.6"
DESCRIPTION = "Right
              ascension of spacecraft z
              axis."
UNIT       = "rad"
VALID_MINIMUM = 0.0
VALID_MAXIMUM = 6.283185
END_OBJECT  = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 73
BYTES      = 9
DATA_TYPE  = ASCII_REAL
NAME       =
              "SC_ATT_ANGLE_DEC"
FORMAT     = "F9.6"
DESCRIPTION = "Declination
              of spacecraft z axis."
UNIT       = "rad"
VALID_MINIMUM = -1.5708
VALID_MAXIMUM = 1.5708
END_OBJECT  = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 74
BYTES      = 9
DATA_TYPE  = ASCII_REAL
NAME       =
              "SC_ATT_ANGLE_TW"
FORMAT     = "F9.6"
DESCRIPTION = "Rotation of
              spacecraft about z axis."
UNIT       = "rad"
VALID_MINIMUM = 0.0
VALID_MAXIMUM = 6.283185
END_OBJECT  = FIELD

```

```
OBJECT          = FIELD
FIELD_NUMBER    = 75
BYTES           = 6
DATA_TYPE       = ASCII_INTEGER
NAME            = "C1COUNTS"
FORMAT          = "I6"
DESCRIPTION     = "High
sensitivity counts."
VALID_MINIMUM   = 0
VALID_MAXIMUM   = 1000000
END_OBJECT      = FIELD
```

```
OBJECT          = FIELD
FIELD_NUMBER    = 76
BYTES           = 6
DATA_TYPE       = ASCII_INTEGER
NAME            = "C2COUNTS"
FORMAT          = "I6"
DESCRIPTION     = "Low
sensitivity counts."
VALID_MINIMUM   = 0
VALID_MAXIMUM   = 1000000
END_OBJECT      = FIELD
```

**APPENDIX E: HKG STRUCTURE FILE CONTENTS**

```

OBJECT      = FIELD
  FIELD_NUMBER = 1
  NAME        = "nOriginalPacketID"
  BYTES      = 10
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I10"
  DESCRIPTION = "The unique
                database ID of the packet"
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 2
  NAME        = "nEventID"
  BYTES      = 10
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I10"
  DESCRIPTION = "The ID that
                references the INMSDB data
                event the telemetry packet
                belongs to"
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 3
  NAME        = "nAssocSciOrigpacketID"
  BYTES      = 10
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I10"
  DESCRIPTION = "The
                associated science packet
                (the nearest science
                packet chronologically) for
                this HK packet. ** Not
                currently used."
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 4
  NAME        = "tScclkTime"
  BYTES      = 23
  DATA_TYPE  = CHARACTER
  FORMAT     = "A23"
  DESCRIPTION = "The
                spacecraft clock time of
                the packet - does not
                include milliseconds (see
                NSCLKMillis below for
                milliseconds)"
END_OBJECT  = FIELD

```

```

OBJECT      = FIELD
  FIELD_NUMBER = 5
  NAME        = "dScclkRaw"
  BYTES      = 15
  DATA_TYPE  = ASCII_REAL
  FORMAT     = "F15.1"
  DESCRIPTION = "The raw
                spacecraft clock time that
                TSCLKTIME and NSCLKMillis
                were generated from"
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 6
  NAME        = "tErtTime"
  BYTES      = 23
  DATA_TYPE  = CHARACTER
  FORMAT     = "A23"
  DESCRIPTION = "The Earth
                Receive Time - the time the
                packet was received from a
                NASA DSN station"
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 7
  NAME        = "tProcessedTime"
  BYTES      = 23
  DATA_TYPE  = CHARACTER
  FORMAT     = "A23"
  DESCRIPTION = "The UTC time
                the packet was processed by
                the INMS data system"
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 8
  NAME        = "sMode"
  BYTES      = 10
  DATA_TYPE  = CHARACTER
  FORMAT     = "A10"
  DESCRIPTION = "Packet mode,
                indicates if the packet is
                data or synthetic test
                data"
END_OBJECT  = FIELD

```

```

OBJECT      = FIELD
  FIELD_NUMBER = 9
  NAME        = "bValid"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I1"
  DESCRIPTION = "Indicates
                 that the packet is a valid
                 packet"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 10
  NAME        = "nInstMode"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I1"
  DESCRIPTION = "Specifies the
                 instrument operating mode"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 7
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 11
  NAME        =
    "nSequenceTable"
  BYTES      = 2
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I2"
  DESCRIPTION = "Sequence
                 table number"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 31
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 12
  NAME        = "nCycleIndex"
  BYTES      = 2
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I2"
  DESCRIPTION = "Index of the
                 cycle table entry"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 15
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 13
  NAME        = "nScanIndex"
  BYTES      = 2
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I2"
  DESCRIPTION = "The number of
                 the scan within the cycle"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 15
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 14
  NAME        = "nElapsedTime"
  BYTES      = 5
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I5"
  DESCRIPTION = "The time
                 elapsed since the start of
                 the current sequence
                 table"
  UNIT       = "s"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 65535
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 15
  NAME        = "nCycleTable"
  BYTES      = 2
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I2"
  DESCRIPTION = "Cycle table
                 number"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 63
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 16
  NAME        = "nspare1"
  BYTES      = 17
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I2"
  DESCRIPTION = "2-bit field.
                 LSB=ScanIndex MSB,
                 MSB=CycleIndex MSB"
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 17
  NAME        = "nDataSumN"
  BYTES      = 3
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I3"
  DESCRIPTION = "Number of
    mass scans being co-added
    to reduce telemetry
    requirements"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 255
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 18
  NAME        = "nThermStatus"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I1"
  DESCRIPTION = "Thermistor
    test status. Performed
    before pressure BA test.
    Only valid prior to cover
    removal."
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 3
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 19
  NAME        = "nThermDelta"
  BYTES      = 4
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I4"
  DESCRIPTION = "Thermistor
    pressure AMUX value. Amux
    ID=49. Valid only prior to
    cover removal."
  VALID_MINIMUM = -512
  VALID_MAXIMUM = 512
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 20
  NAME        = "nFswVersion"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I3"
  DESCRIPTION = "Reports the
    flight software version"
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 21
  NAME        = "nBaStatus"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I1"
  DESCRIPTION = "Pressure test
    status, valid only prior to
    cover removal"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 3
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 22
  NAME        = "nBaStep"
  BYTES      = 2
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I2"
  DESCRIPTION = "BA DAC
    emission value. Valid only
    prior to cover removal."
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 15
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 23
  NAME        = "nBaValue"
  BYTES      = 2
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I2"
  DESCRIPTION = "Pressure at
    end of test. Valid only
    prior to cover removal"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 15
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 24
  NAME        = "nTcReceived"
  BYTES      = 3
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I3"
  DESCRIPTION = "Number of
    telecommands received"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 255
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 25
  NAME        = "nAlfReceived"
  BYTES       = 3
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I3"
  DESCRIPTION = "Indicates a
    BIU bus error"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 255
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 26
  NAME        = "nAlfRejected"
  BYTES       = 2
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I2"
  DESCRIPTION = "Indicates a
    1750 machine error"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 15
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 27
  NAME        = "nTcRejected"
  BYTES       = 2
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I2"
  DESCRIPTION = "Number of
    telecommads rejected"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 15
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 28
  NAME        = "nInstTmMode"
  BYTES       = 3
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I3"
  DESCRIPTION = "Telmetry mode
    index"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 255
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 29
  NAME        = "nBiuSpare1"
  BYTES       = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I1"
  DESCRIPTION = "Readback of
    BIU discretes 6 and 7"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 3
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 30
  NAME        = "bTgordt"
  BYTES       = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I1"
  DESCRIPTION = "Readback of
    Flight computer boot mode
    discrete"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 31
  NAME        = "bAlfOverInhibit"
  BYTES       = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I1"
  DESCRIPTION = "Readback of
    ALF override inhibit
    discrete"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 32
  NAME        =
    "bAlfBootEnable"
  BYTES       = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I1"
  DESCRIPTION = "Readback of
    ALF boot enable discrete"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```



```

OBJECT      = FIELD
FIELD_NUMBER = 33
NAME        =
  "bDefSciEnable"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "Readback of
  default science enable
  discrete"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 34
NAME        = "bBiuSleep"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "readback of
  sleep discrete"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 35
NAME        = "bBiuPord0"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "readback of
  BIU discrete 0"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 36
NAME        = "bHkFull"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "BIU error
  flag set when housekeeping
  tm buffer is full"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 37
NAME        = "bHkSsysf"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "BIU error
  flag set when subsystem
  fail bit is set in 1553
  status word"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 38
NAME        = "bHkMsgError"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "BIU error
  flag set when message error
  bit is set in 1553 status
  word"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 39
NAME        = "bTmScError"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "BIU error
  flag set when the number
  words expected in 1553
  receive sub-address 29 is
  incorrect"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 40
NAME        = "bStTblError"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "BIU error
  flag set when the number
  words expected in 1553
  receive sub-address 19 is
  incorrect"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 41
  NAME        = "bAncbcError"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I1"
  DESCRIPTION = "BIU error
                flag set when the number
                words expected in 1553
                receive sub-address 10 is
                incorrect"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 42
  NAME        = "bbiuspare2"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I1"
  DESCRIPTION = "spare, always
                0"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 43
  NAME        = "bRtiSfail"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I1"
  DESCRIPTION = "Set when no
                RTIs have been received for
                2 seconds"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 44
  NAME        = "bFil10n"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I1"
  DESCRIPTION = "State of
                primary open source
                filament"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

```

```

OBJECT      = FIELD
  FIELD_NUMBER = 45
  NAME        = "bFil20n"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I1"
  DESCRIPTION = "State of
                secondary open source
                filament"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 46
  NAME        = "bFil30n"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I1"
  DESCRIPTION = "State of
                primary closed source
                filament"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 47
  NAME        = "bFil40n"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I1"
  DESCRIPTION = "State of
                secondary closed source
                filament"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 48
  NAME        = "bDconSpare1"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I1"
  DESCRIPTION = "spare"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

```

```

OBJECT      = FIELD
  FIELD_NUMBER = 49
  NAME        = "bFil60n"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I1"
  DESCRIPTION = "State of BA
                pressure gauge filament"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 50
  NAME        = "nDconSpare2"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I1"
  DESCRIPTION = "spare"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 3
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 51
  NAME        = "bBiuWdx"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I1"
  DESCRIPTION = "BIU watchdog
                timer status, 1(ok)
                0(expired)"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 52
  NAME        = "bBiuFt"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I1"
  DESCRIPTION = "BIU write
                status, set to 0 when a BIU
                bus timeout is detected in
                boot code"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

```

```

OBJECT      = FIELD
  FIELD_NUMBER = 53
  NAME        = "bFcft"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I1"
  DESCRIPTION = "BIU write
                status, set to 0 when a CPU
                Machine Error is detected
                in boot code"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 54
  NAME        = "bFctGo"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I1"
  DESCRIPTION = "BIU write
                status, set when TGO reset
                indicator latch is set on
                bootup. Always set to 0 in
                TM."
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 55
  NAME        = "bFcillad"
  BYTES      = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT     = "I1"
  DESCRIPTION = "BIU write
                status, set to 0 when CPU
                accesses an illegal
                address. Always set to 0
                in TM."
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

```

```
OBJECT      = FIELD
FIELD_NUMBER = 56
NAME        = "bFcpu"
BYTES      = 1
DATA_TYPE   = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "BIU write
              status, set to 1 when CPU
              completes a normal power
              up. Always set to 0 in
              TM."
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT   = FIELD
```

```
OBJECT      = FIELD
FIELD_NUMBER = 57
NAME        = "bFcsuren"
BYTES      = 1
DATA_TYPE   = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "BIU write
              status, set to 0 when CPU
              start-up RAM is enabled.
              Always set to 0 in TM."
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT   = FIELD
```

```
OBJECT      = FIELD
FIELD_NUMBER = 58
NAME        =
    "bBiuDtsLoaded"
BYTES      = 1
DATA_TYPE   = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "BIU write
              status, set to 1 when BIU
              descriptor table is loaded
              on bootup."
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT   = FIELD
```

```
OBJECT      = FIELD
FIELD_NUMBER = 59
NAME        = "d1emission"
BYTES      = 7
DATA_TYPE   = ASCII_REAL
FORMAT     = "F7.4"
DESCRIPTION = "Emission
              Current of primary open
              source filament"
UNIT       = "uA"
VALID_MINIMUM = -0.5
VALID_MAXIMUM = 25.75
END_OBJECT   = FIELD
```

```
OBJECT      = FIELD
FIELD_NUMBER = 60
NAME        = "d2emission"
BYTES      = 8
DATA_TYPE   = ASCII_REAL
FORMAT     = "F8.5"
DESCRIPTION = "Emission
              Current of secondary open
              source filament"
UNIT       = "uA"
VALID_MINIMUM = 0.05
VALID_MAXIMUM = 25.75
END_OBJECT   = FIELD
```

```
OBJECT      = FIELD
FIELD_NUMBER = 61
NAME        = "dImon1"
BYTES      = 8
DATA_TYPE   = ASCII_REAL
FORMAT     = "F8.6"
DESCRIPTION = "Input
              current"
UNIT       = "A"
VALID_MINIMUM = 0.0
VALID_MAXIMUM = 1.75
END_OBJECT   = FIELD
```

```
OBJECT      = FIELD
FIELD_NUMBER = 62
NAME        = "dGround1"
BYTES      = 5
DATA_TYPE   = ASCII_REAL
FORMAT     = "F5.2"
DESCRIPTION = "Ground
              reference voltage"
UNIT       = "V"
VALID_MINIMUM = -0.05
VALID_MAXIMUM = 5.1
END_OBJECT   = FIELD
```

```
OBJECT      = FIELD
FIELD_NUMBER = 63
NAME        = "d1Current"
BYTES      = 8
DATA_TYPE   = ASCII_REAL
FORMAT     = "F8.5"
DESCRIPTION = "Primary open
              source filament current"
UNIT       = "A"
VALID_MINIMUM = -0.1
VALID_MAXIMUM = 1.5
END_OBJECT   = FIELD
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 64
  NAME        = "d2Current"
  BYTES      = 8
  DATA_TYPE  = ASCII_REAL
  FORMAT     = "F8.5"
  DESCRIPTION = "Secondary
    open source filament
    current"
  UNIT       = "A"
  VALID_MINIMUM = -0.1
  VALID_MAXIMUM = 1.5
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 65
  NAME        = "d1Target"
  BYTES      = 8
  DATA_TYPE  = ASCII_REAL
  FORMAT     = "F8.5"
  DESCRIPTION = "Primary open
    source anode current"
  UNIT       = "uA"
  VALID_MINIMUM = -0.5
  VALID_MAXIMUM = 27.75
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 66
  NAME        = "d2Target"
  BYTES      = 8
  DATA_TYPE  = ASCII_REAL
  FORMAT     = "F8.5"
  DESCRIPTION = "Secondary
    open source anode current"
  UNIT       = "uA"
  VALID_MINIMUM = -0.5
  VALID_MAXIMUM = 27.75
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 67
  NAME        = "d1Bias50"
  BYTES      = 5
  DATA_TYPE  = ASCII_REAL
  FORMAT     = "F5.2"
  DESCRIPTION = "Open Source
    +40V Bias Oscillator Drive
    Current "
  UNIT       = "V"
  VALID_MINIMUM = -0.05
  VALID_MAXIMUM = 5.1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 68
  NAME        = "d1Bias70"
  BYTES      = 5
  DATA_TYPE  = ASCII_REAL
  FORMAT     = "F5.2"
  DESCRIPTION = "Open Source
    primary Filament Bias
    Oscillator Drive Current"
  UNIT       = "V"
  VALID_MINIMUM = -0.05
  VALID_MAXIMUM = 5.1
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 69
  NAME        = "d2Bias70"
  BYTES      = 5
  DATA_TYPE  = ASCII_REAL
  FORMAT     = "F5.2"
  DESCRIPTION = "Open Source
    secondary Filament Bias
    Oscillator Drive Current"
  UNIT       = "V"
  VALID_MINIMUM = -0.05
  VALID_MAXIMUM = 5.1
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 70
  NAME        = "dGround2"
  BYTES      = 5
  DATA_TYPE  = ASCII_REAL
  FORMAT     = "F5.2"
  DESCRIPTION = "Ground
    reference voltage"
  UNIT       = "V"
  VALID_MINIMUM = -0.05
  VALID_MAXIMUM = 5.1
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 71
  NAME        = "dAmString"
  BYTES      = 9
  DATA_TYPE  = ASCII_REAL
  FORMAT     = "F9.4"
  DESCRIPTION = "AM Board
    Resistor Divider String
    Current"
  UNIT       = "V"
  VALID_MINIMUM = -645.
  VALID_MAXIMUM = 5.1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 72
NAME        = "dFbString"
BYTES      = 9
DATA_TYPE   = ASCII_REAL
FORMAT     = "F9.4"
DESCRIPTION = "FB Board
              Resistor Divider String
              Current"
UNIT       = "V"
VALID_MINIMUM = -513.
VALID_MAXIMUM = 4.1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 73
NAME        = "dBaCollector"
BYTES      = 5
DATA_TYPE   = ASCII_REAL
FORMAT     = "F5.2"
DESCRIPTION = "BA pressure
              gage collector current"
UNIT       = "V"
VALID_MINIMUM = -0.05
VALID_MAXIMUM = 5.1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 74
NAME        = "dFbControl"
BYTES      = 5
DATA_TYPE   = ASCII_REAL
FORMAT     = "F5.2"
DESCRIPTION = "-390V
              Regulator Control Voltage "
UNIT       = "V"
VALID_MINIMUM = -0.05
VALID_MAXIMUM = 5.1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 75
NAME        = "d3Emission"
BYTES      = 8
DATA_TYPE   = ASCII_REAL
FORMAT     = "F8.5"
DESCRIPTION = "Emission
              Current of primary closed
              source filament"
UNIT       = "uA"
VALID_MINIMUM = -0.5
VALID_MAXIMUM = 25.75
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  
```

```

FIELD_NUMBER = 76
NAME        = "d4Emission"
BYTES      = 8
DATA_TYPE   = ASCII_REAL
FORMAT     = "F8.5"
DESCRIPTION = "Emission
              Current of secondary closed
              source filament"
UNIT       = "uA"
VALID_MINIMUM = -0.5
VALID_MAXIMUM = 25.75
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 77
NAME        = "dImon2"
BYTES      = 8
DATA_TYPE   = ASCII_REAL
FORMAT     = "F8.6"
DESCRIPTION = "Input
              current"
UNIT       = "A"
VALID_MINIMUM = 0.0
VALID_MAXIMUM = 1.75
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 78
NAME        = "dEb4_4"
BYTES      = 5
DATA_TYPE   = ASCII_REAL
FORMAT     = "F5.2"
DESCRIPTION = "anode 3
              current monitor in volts"
UNIT       = "V"
VALID_MINIMUM = -0.05
VALID_MAXIMUM = 5.1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 79
NAME        = "d3Current"
BYTES      = 8
DATA_TYPE   = ASCII_REAL
FORMAT     = "F8.5"
DESCRIPTION = "Primary
              closed source filament
              current"
UNIT       = "A"
VALID_MINIMUM = -0.5
VALID_MAXIMUM = 1.5
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 80
NAME        = "d4Current"
BYTES      = 8
DATA_TYPE   = ASCII_REAL
FORMAT     = "F8.5"
DESCRIPTION = "Secondary
              closed source filament
              current"
UNIT       = "A"
VALID_MINIMUM = -0.5
VALID_MAXIMUM = 1.5
END_OBJECT  = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 81
NAME        = "d4Anode"
BYTES      = 8
DATA_TYPE   = ASCII_REAL
FORMAT     = "F8.5"
DESCRIPTION = "Primary
              closed source anode
              current"
UNIT       = "uA"
VALID_MINIMUM = -0.1
VALID_MAXIMUM = 10.2
END_OBJECT  = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 82
NAME        = "d3Anode"
BYTES      = 8
DATA_TYPE   = ASCII_REAL
FORMAT     = "F8.5"
DESCRIPTION = "Secondary
              closed source anode
              current"
UNIT       = "uA"
VALID_MINIMUM = -0.1
VALID_MAXIMUM = 10.2
END_OBJECT  = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 83
NAME        = "d3Bias50"
BYTES      = 5
DATA_TYPE   = ASCII_REAL
FORMAT     = "F5.2"
DESCRIPTION = "Closed Source
              +40V Bias Oscillator Drive
              Current"
UNIT       = "V"
VALID_MINIMUM = -0.05
VALID_MAXIMUM = 5.1
END_OBJECT  = FIELD

```

```

OBJECT      = FIELD
FIELD_NUMBER = 84
NAME        = "d3Bias70"
BYTES      = 5
DATA_TYPE   = ASCII_REAL
FORMAT     = "F5.2"
DESCRIPTION = "Closed
              Source primary Filament
              Bias Oscillator Drive
              Current"
UNIT       = "V"
VALID_MINIMUM = -0.05
VALID_MAXIMUM = 5.1
END_OBJECT  = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 85
NAME        = "d4Bias70"
BYTES      = 5
DATA_TYPE   = ASCII_REAL
FORMAT     = "F5.2"
DESCRIPTION = "Closed
              Source secondary Filament
              Bias Oscillator Drive
              Current"
UNIT       = "V"
VALID_MINIMUM = -0.05
VALID_MAXIMUM = 5.1
END_OBJECT  = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 86
NAME        =
              "dRfSupplyTemp"
BYTES      = 9
DATA_TYPE   = ASCII_REAL
FORMAT     = "F9.6"
DESCRIPTION = "RF power
              supply temperature"
UNIT       = "C"
VALID_MINIMUM = 13.
VALID_MAXIMUM = 32.5
END_OBJECT  = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 87
NAME        =
              "dFbSupplyTemp"
BYTES      = 9
DATA_TYPE   = ASCII_REAL
FORMAT     = "F9.6"
DESCRIPTION = "FB Board
              temperature"
UNIT       = "C"
VALID_MINIMUM = 13.
VALID_MAXIMUM = 32.5
END_OBJECT  = FIELD

```

```

OBJECT      = FIELD
FIELD_NUMBER = 88
NAME        =
  "dEmSupplyTemp"
BYTES      = 9
DATA_TYPE  = ASCII_REAL
FORMAT     = "F9.6"
DESCRIPTION = "EM Board
  temperature"
UNIT       = "C"
VALID_MINIMUM = 13.
VALID_MAXIMUM = 32.5
END_OBJECT = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 89
NAME        = "dPlus5Fb"
BYTES      = 5
DATA_TYPE  = ASCII_REAL
FORMAT     = "F5.2"
DESCRIPTION = "Thermister +5
  reference voltage"
UNIT       = "V"
VALID_MINIMUM = -0.05
VALID_MAXIMUM = 5.1
END_OBJECT = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 90
NAME        = "dBaGrid"
BYTES      = 8
DATA_TYPE  = ASCII_REAL
FORMAT     = "F8.4"
DESCRIPTION = "BA pressure
  gage grid current"
UNIT       = "uA"
VALID_MINIMUM = -2.
VALID_MAXIMUM = 152.
END_OBJECT = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 91
NAME        = "d011"
BYTES      = 8
DATA_TYPE  = ASCII_REAL
FORMAT     = "F8.5"
DESCRIPTION = "Open Lens 1
  (CEU) Current"
UNIT       = "uA"
VALID_MINIMUM = -0.1
VALID_MAXIMUM = 6.8
END_OBJECT = FIELD

```

```

OBJECT      = FIELD
FIELD_NUMBER = 92
NAME        = "d012"
BYTES      = 8
DATA_TYPE  = ASCII_REAL
FORMAT     = "F8.5"
DESCRIPTION = "Open Lens 2
  (CEU) Current "
UNIT       = "uA"
VALID_MINIMUM = -0.1
VALID_MAXIMUM = 6.8
END_OBJECT = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 93
NAME        = "dBaCurrent"
BYTES      = 9
DATA_TYPE  = ASCII_REAL
FORMAT     = "F9.6"
DESCRIPTION = "BA pressure
  gage filament current"
UNIT       = "A RMS"
VALID_MINIMUM = -0.05
VALID_MAXIMUM = 1.4
END_OBJECT = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 94
NAME        = "dBaEmission"
BYTES      = 8
DATA_TYPE  = ASCII_REAL
FORMAT     = "F8.4"
DESCRIPTION = "BA pressure
  gage emission current"
UNIT       = "uA"
VALID_MINIMUM = -1.6
VALID_MAXIMUM = 193.75
END_OBJECT = FIELD

OBJECT      = FIELD
FIELD_NUMBER = 95
NAME        = "dGround3"
BYTES      = 5
DATA_TYPE  = ASCII_REAL
FORMAT     = "F5.2"
DESCRIPTION = "Ground
  reference voltage"
UNIT       = "V"
VALID_MINIMUM = -0.5
VALID_MAXIMUM = 5.1
END_OBJECT = FIELD

```



OBJECT = FIELD  
 FIELD\_NUMBER = 96  
 NAME = "dBaBias"  
 BYTES = 5  
 DATA\_TYPE = ASCII\_REAL  
 FORMAT = "F5.2"  
 DESCRIPTION = "BA pressure  
 gage bias oscillator drive  
 current"  
 UNIT = "V"  
 VALID\_MINIMUM = -0.5  
 VALID\_MAXIMUM = 5.1  
 END\_OBJECT = FIELD

OBJECT = FIELD  
 FIELD\_NUMBER = 97  
 NAME = "dRfAgc"  
 BYTES = 5  
 DATA\_TYPE = ASCII\_REAL  
 FORMAT = "F5.2"  
 DESCRIPTION = "RF automatic  
 gain control monitor  
 voltage"  
 UNIT = "V"  
 VALID\_MINIMUM = -0.5  
 VALID\_MAXIMUM = 5.1  
 END\_OBJECT = FIELD

OBJECT = FIELD  
 FIELD\_NUMBER = 98  
 NAME = "dMinus5\_7"  
 BYTES = 7  
 DATA\_TYPE = ASCII\_REAL  
 FORMAT = "F7.4"  
 DESCRIPTION = "Monitor -5.7  
 Volt supply"  
 UNIT = "V"  
 VALID\_MINIMUM = -7.  
 VALID\_MAXIMUM = 5.2  
 END\_OBJECT = FIELD

OBJECT = FIELD  
 FIELD\_NUMBER = 99  
 NAME = "dFcTemp"  
 BYTES = 9  
 DATA\_TYPE = ASCII\_REAL  
 FORMAT = "F9.6"  
 DESCRIPTION = "Flight  
 computer board temperature"  
 UNIT = "C"  
 VALID\_MINIMUM = 18.5  
 VALID\_MAXIMUM = 36.75  
 END\_OBJECT = FIELD

OBJECT = FIELD  
 FIELD\_NUMBER = 100  
 NAME = "dLvpStemp"  
 BYTES = 9  
 DATA\_TYPE = ASCII\_REAL  
 FORMAT = "F9.6"  
 DESCRIPTION = "Low voltage  
 power supply frame  
 temperature"  
 UNIT = "C"  
 VALID\_MINIMUM = 23.25  
 VALID\_MAXIMUM = 31.25  
 END\_OBJECT = FIELD

OBJECT = FIELD  
 FIELD\_NUMBER = 101  
 NAME = "dEm1Current"  
 BYTES = 7  
 DATA\_TYPE = ASCII\_REAL  
 FORMAT = "F7.4"  
 DESCRIPTION = "Electron  
 multiplier 1 current  
 monitor"  
 UNIT = "KV"  
 VALID\_MINIMUM = -0.5  
 VALID\_MAXIMUM = 38.1  
 END\_OBJECT = FIELD

OBJECT = FIELD  
 FIELD\_NUMBER = 102  
 NAME = "dEm2Current"  
 BYTES = 7  
 DATA\_TYPE = ASCII\_REAL  
 FORMAT = "F7.4"  
 DESCRIPTION = "Electron  
 multiplier 2 current  
 monitor"  
 UNIT = "KV"  
 VALID\_MINIMUM = -0.5  
 VALID\_MAXIMUM = 38.1  
 END\_OBJECT = FIELD

OBJECT = FIELD  
 FIELD\_NUMBER = 103  
 NAME = "dImon3"  
 BYTES = 8  
 DATA\_TYPE = ASCII\_REAL  
 FORMAT = "F8.6"  
 DESCRIPTION = "Input  
 current"  
 UNIT = "A"  
 VALID\_MINIMUM = 0.0  
 VALID\_MAXIMUM = 1.75  
 END\_OBJECT = FIELD

```

OBJECT      = FIELD
FIELD_NUMBER = 104
NAME        = "dMultAna1"
BYTES      = 5
DATA_TYPE  = ASCII_REAL
FORMAT     = "F5.2"
DESCRIPTION = "Pulse Amp 1
              Analog Voltage Proportional
              to Input Frequency "
UNIT       = "uA"
VALID_MINIMUM = -0.1
VALID_MAXIMUM = 10.2
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 105
NAME        = "dMultAna2"
BYTES      = 6
DATA_TYPE  = ASCII_REAL
FORMAT     = "F6.3"
DESCRIPTION = "Pulse Amp 2
              Analog Voltage Proportional
              to Input Frequency "
UNIT       = "uA"
VALID_MINIMUM = -0.05
VALID_MAXIMUM = 1.75
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 106
NAME        = "dPlus5r"
BYTES      = 5
DATA_TYPE  = ASCII_REAL
FORMAT     = "F5.2"
DESCRIPTION = "Monitor 5R
              voltage"
UNIT       = "V"
VALID_MINIMUM = -0.1
VALID_MAXIMUM = 10.2
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 107
NAME        =
              "dThermPressInt"
BYTES      = 5
DATA_TYPE  = ASCII_REAL
FORMAT     = "F5.2"
DESCRIPTION = "Internal BA
              pressure gage temperature"
UNIT       = "V"
VALID_MINIMUM = -0.05
VALID_MAXIMUM = 5.1
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 108
NAME        =
              "dThermPressExt"
BYTES      = 5
DATA_TYPE  = ASCII_REAL
FORMAT     = "F5.2"
DESCRIPTION = "External BA
              pressure gage temperature"
UNIT       = "V"
VALID_MINIMUM = -0.05
VALID_MAXIMUM = 5.1
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 109
NAME        = "dPlus13"
BYTES      = 7
DATA_TYPE  = ASCII_REAL
FORMAT     = "F7.4"
DESCRIPTION = "Monitor +13
              voltage"
UNIT       = "V"
VALID_MINIMUM = -0.2
VALID_MAXIMUM = 14.75
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 110
NAME        = "nIndex"
BYTES      = 3
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I3"
DESCRIPTION = "AMUX index of
              first channel sampled for
              latest scan."
VALID_MINIMUM = 0
VALID_MAXIMUM = 255
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 111
NAME        = "dRfFreq"
BYTES      = 5
DATA_TYPE  = ASCII_REAL
FORMAT     = "F5.3"
DESCRIPTION = "Frequency
              monitor"
VALID_MINIMUM = 0.0
VALID_MAXIMUM = 0.22
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 112
NAME        =
  "nCpuIdleCounter"
BYTES      = 2
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I2"
DESCRIPTION = "Flight
  computer heartbeat counter"
VALID_MINIMUM = 0
VALID_MAXIMUM = 15
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 113
NAME        = "bDisc0Reset"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "Set to 1 on
  bootup to indicate last CPU
  reset was due to BIU
  discrete 0."
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 114
NAME        = "bAllSysGo"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "Master INMS
  error flag"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 115
NAME        =
  "bAllSysGoLatched"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "Latched
  version of master INMS
  error flag"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 116
NAME        =
  "bExcNoHandler"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "unhandled
  exception occurred "
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 117
NAME        = "bSafeMode"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "not used"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 118
NAME        = "bForcedSleep"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "Indicates the
  instrument entered Sleep
  state due to detected high
  value on IMONs"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 119
NAME        = "bBiuAutoInit"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "3-bit field
  that counts BIU auto-
  initializations."
END_OBJECT = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 120
  NAME        = "bGseTest"
  BYTES       = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I1"
  DESCRIPTION = "not used"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 121
  NAME        = "bSystemInitialized"
  BYTES       = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I1"
  DESCRIPTION = "Indicates
  system initialization
  complete"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 122
  NAME        = "bSystemConfigured"
  BYTES       = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I1"
  DESCRIPTION = "Indicates
  system configuration is
  complete"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 123
  NAME        = "bTgoDetect"
  BYTES       = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I1"
  DESCRIPTION = "Readout of
  watchdog reset latch on FC
  board during bootup.
  Usually set to 1 -
  unreliable indicator."
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

```

```

OBJECT      = FIELD
  FIELD_NUMBER = 124
  NAME        = "bBiuResetToCc"
  BYTES       = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I1"
  DESCRIPTION = "Indicates
  that a BIU reset has
  occurred"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 125
  NAME        = "bIcError"
  BYTES       = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I1"
  DESCRIPTION = "Set to 1 on
  bootup if reset is due to
  wayward instruction
  counter (jump to location
  0)."
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 126
  NAME        = "bTgoToggle"
  BYTES       = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I1"
  DESCRIPTION = "Toggled
  between 1 and 0 each time
  the Watchdog Reset Task
  executes"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

OBJECT      = FIELD
  FIELD_NUMBER = 127
  NAME        = "nSubModuleID"
  BYTES       = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I2"
  DESCRIPTION = "Ada exception
  sub-module ID (CSU)
  0=SciPkt, 1= Usid,
  4=UseqISR, 8=USIDLostSync"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD

```

```

OBJECT          = FIELD
FIELD_NUMBER    = 128
NAME            = "nTrapFlag"
BYTES          = 1
DATA_TYPE      = ASCII_INTEGER
FORMAT        = "I1"
DESCRIPTION    = "Ada
  exception/error type:
  0=Trace_Trap, 1=Error_Trap,
  2=Exception_Trap"
VALID_MINIMUM  = 0
VALID_MAXIMUM  = 3
END_OBJECT     = FIELD
  
```

```

OBJECT          = FIELD
FIELD_NUMBER    = 129
NAME            = "nModuleId"
BYTES          = 1
DATA_TYPE      = ASCII_INTEGER
FORMAT        = "I2"
DESCRIPTION    = "Ada exception
  module ID (CSC)
  1=INMS_Exec, 2=INMS_Init,
  3=AMux_IO, 4=DMux_IO,
  5=DCon_IO, 6=CDS_IO,
  7=Useq_IO, 8-10=spare,
  11=Filament Control, 12=Ion
  Source Select Control,
  13=Ion Focus Control, 14=HV
  Focus Control, 15=Quad Rod
  Control, 16=Ion Det.
  Control, 17=Ion Pump
  Control, 18=Pressure Sensor
  Monitor, 19=Power Supply
  Monitor, 20=Micro-Sequencer
  Control"
VALID_MINIMUM  = 0
VALID_MAXIMUM  = 63
END_OBJECT     = FIELD
  
```

```

OBJECT          = FIELD
FIELD_NUMBER    = 130
NAME            = "bInmsBitFail"
BYTES          = 1
DATA_TYPE      = ASCII_INTEGER
FORMAT        = "I1"
DESCRIPTION    = "Bootstrap
  Built-in-Test results"
VALID_MINIMUM  = 0
VALID_MAXIMUM  = 1
END_OBJECT     = FIELD
  
```

```

OBJECT          = FIELD
FIELD_NUMBER    = 131
NAME            =
  "bTmBuffOvrflw"
BYTES          = 1
DATA_TYPE      = ASCII_INTEGER
FORMAT        = "I1"
DESCRIPTION    = "Set when the
  allotted memory buffer area
  for TM packets would have
  overflowed"
VALID_MINIMUM  = 0
VALID_MAXIMUM  = 1
END_OBJECT     = FIELD
  
```

```

OBJECT          = FIELD
FIELD_NUMBER    = 132
NAME            = "bAlfBoot"
BYTES          = 1
DATA_TYPE      = ASCII_INTEGER
FORMAT        = "I1"
DESCRIPTION    = "Set when an
  ALF Boot is performed"
VALID_MINIMUM  = 0
VALID_MAXIMUM  = 1
END_OBJECT     = FIELD
  
```

```

OBJECT          = FIELD
FIELD_NUMBER    = 133
NAME            = "bAlfError"
BYTES          = 1
DATA_TYPE      = ASCII_INTEGER
FORMAT        = "I1"
DESCRIPTION    = "Set when any
  BIU or ALF error is
  detected during an ALF
  Boot"
VALID_MINIMUM  = 0
VALID_MAXIMUM  = 1
END_OBJECT     = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 134
NAME        = "bBiuMemerror"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "Set when
              background BIU verification
              processing detects a bad
              BIU memory location. No
              longer used."
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 135
NAME        =
              "bOdbfrOverflow"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "Output data
              buffer overflow. Not used"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 136
NAME        =
              "bUseq00ffline"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "Set when
              micro-sequencer output
              communication goes
              offline"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 137
NAME        =
              "bUseqIOffline"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "Set when
              micro-sequencer input
              communication goes
              offline"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 138
NAME        = "bUseqError"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "Set when any
              micro-sequencer error is
              detected"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 139
NAME        = "b1750me"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "Set when the
              1750 Machine Error
              interrupt occurs and FT
              register <> 0400h"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 140
NAME        = "bAmuxError"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "not used"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
FIELD_NUMBER = 141
NAME        = "bCds00ffline"
BYTES      = 1
DATA_TYPE  = ASCII_INTEGER
FORMAT     = "I1"
DESCRIPTION = "Set when
              BIU/CDS output
              communication goes offline"
VALID_MINIMUM = 0
VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 142
  NAME        = "bCdsIOOffline"
  BYTES       = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I1"
  DESCRIPTION = "Set when
    BIU/CDS input communication
    goes offline"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 143
  NAME        = "bCdsError"
  BYTES       = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I1"
  DESCRIPTION = "set if one or
    more of 1750ME, CDS0Offline
    or CDSiOffline are set"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 144
  NAME        = "bRteError"
  BYTES       = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I1"
  DESCRIPTION = "Set any time
    bootstrap or RTE processing
    detects any of the
    following errors: 1750 BIT
    Fail; Any Memory Test
    fails; Unhandled
    Exceptions; Machine Error;
    TGO Reset or Wayward IC
    Reboot"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 145
  NAME        = "nMemChecksum"
  BYTES       = 1
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I1"
  DESCRIPTION = " memory
    checksum error flag in FSW
    Version 8 or later 0(ok)
    1(bad checksum)"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 1
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 146
  NAME        = "nStmCounter"
  BYTES       = 3
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I3"
  DESCRIPTION = "Count of
    spacecraft tm mode message
    received (1 per second)"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 255
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 147
  NAME        = "nRtiCounter"
  BYTES       = 3
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I3"
  DESCRIPTION = "Count of RTIs
    processed"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 255
END_OBJECT  = FIELD
  
```

```

OBJECT      = FIELD
  FIELD_NUMBER = 148
  NAME        = "nMassTable"
  BYTES       = 3
  DATA_TYPE  = ASCII_INTEGER
  FORMAT      = "I3"
  DESCRIPTION = "value of
    initial mass in current
    mass table"
  VALID_MINIMUM = 0
  VALID_MAXIMUM = 255
END_OBJECT  = FIELD
  
```

```
OBJECT          = FIELD
FIELD_NUMBER    = 149
NAME            = "nCmdSerno1"
BYTES           = 3
DATA_TYPE       = ASCII_INTEGER
FORMAT          = "I3"
DESCRIPTION     = "Serial Number
                  and Time of the telecommand
                  that is being
                  acknowledged. Only two are
                  maintained for each
                  Packet"
VALID_MINIMUM   = 0
VALID_MAXIMUM   = 255
END_OBJECT      = FIELD
```

```
OBJECT          = FIELD
FIELD_NUMBER    = 150
NAME            =
                  "nSclkMilliSec"
BYTES           = 9
DATA_TYPE       = ASCII_INTEGER
FORMAT          = "I9"
DESCRIPTION     = "The
                  milliseconds of the time of
                  the packet. When used in
                  combination with TSCLKTIME
                  produces the exact
                  spacecraft clock time the
                  packet was generated"
END_OBJECT      = FIELD
```